

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20 MG,STKQ1A00
User ID :	sj97904	Batch NO. :	KQM2501920
Print Interval :	50000 Tablets	Running Time :	01 Hour 36 Min 33 Sec
Total Counter :	350176	Total Running Time :	1579 Hour 28 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	22	%	Manual ;	18	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		25	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	15.76	kN	No		
HEP :	25.0 %	15.15	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	12.36	kN	Yes 15	Times	
Ref :		12.12	kN			
LCP :	2.0 %	11.88	kN	Yes 15	Times	
LEP :	25.0 %	9.09	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	8.48	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.95	kN	Min :	2.12	kN	Punch NO.;	49
SD :	9.20	%	Max :	3.58	kN	Punch NO.;	27
Mean Main Pressure :	15.68	kN	Min :	11.78	kN	Punch NO.;	33
SD :	8.40	%	Max :	18.74	kN	Punch NO.;	11
Filling Depth :	Increase ;	462	Times	Decrease ;	446	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	5	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.10	mm	Pre Thickness ;	1.10	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.55	mm	Main Thickness ;	0.55	mm
Filling Depth :	6.55	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.749	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	23	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.05	kN		
	Max ;	0.13	kN	Max Punch ;	4
Lower Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Ejection Force :	Average ;	0.18	kN		
	Max ;	0.31	kN	Max Punch ;	45

Tablet Data (N/A)

Total Counter :	350176	Tablets			
A.W.C Counter :	321756	Tablets			
HEP :	2289 (0.7%)	Tablets	LEP :	1842 (0.6%)	Tablets
GOOD :	317625 (98.7%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20 MG,STKQ1A00
User ID :	sj97904	Batch NO. :	KQM2501920
Print Interval :	50000 Tablets	Running Time :	01 Hour 36 Min 33 Sec
Total Counter :	350176	Total Running Time :	1579 Hour 28 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	18	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		25	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	15.82	kN	No		
HEP :	25.0 %	15.21	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	12.41	kN	Yes 15	Times	
Ref :		12.17	kN			
LCP :	2.0 %	11.93	kN	Yes 15	Times	
LEP :	25.0 %	9.13	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	8.52	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.89	kN	Min :	1.52	kN	Punch NO.;	49
SD :	7.50	%	Max :	2.23	kN	Punch NO.;	27
Mean Main Pressure :	13.04	kN	Min :	9.49	kN	Punch NO.;	33
SD :	7.70	%	Max :	14.70	kN	Punch NO.;	17
Filling Depth :	Increase ;	277	Times	Decrease ;	279	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	4	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.10	mm	Pre Thickness ;	1.10	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.55	mm	Main Thickness ;	0.55	mm
Filling Depth :	6.22	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.749	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	23	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.03	kN		
	Max ;	0.09	kN	Max Punch ;	30
Lower Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Ejection Force :	Average ;	0.18	kN		
	Max ;	0.31	kN	Max Punch ;	45

Tablet Data (N/A)

Total Counter :	350176	Tablets			
A.W.C Counter :	321756	Tablets			
HEP :	2289 (0.7%)	Tablets	LEP :	1842 (0.6%)	Tablets
GOOD :	317625 (98.7%)	Tablets			