

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20 MG,STKQ1A00
User ID :	sj97904	Batch NO. :	KQM2501920
Print Interval :	50000 Tablets	Running Time :	19 Hour 03 Min 00 Sec
Total Counter :	4330260	Total Running Time :	1596 Hour 55 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	22	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		25	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.00	kN	No		
HEP :	30.0 %	18.00	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	14.12	kN	Yes 15	Times	
Ref :		13.84	kN			
LCP :	2.0 %	13.57	kN	Yes 15	Times	
LEP :	30.0 %	9.69	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.69	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.30	kN	Min :	1.92	kN	Punch NO.;	11
SD :	7.20	%	Max :	2.67	kN	Punch NO.;	44
Mean Main Pressure :	13.81	kN	Min :	11.34	kN	Punch NO.;	64
SD :	7.20	%	Max :	15.57	kN	Punch NO.;	28
Filling Depth :	Increase ;	1287	Times	Decrease ;	1390	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	30	RPM	Capacity :	234000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.05	mm	Pre Thickness ;	1.06	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.53	mm	Main Thickness ;	0.53	mm
Filling Depth :	6.34	mm	Current Cam :	Cam B	
Main Air pressure :	0.799	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	23	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.12	kN		
	Max ;	0.19	kN	Max Punch ;	11
Lower Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Ejection Force :	Average ;	0.13	kN		
	Max ;	0.23	kN	Max Punch ;	31

Tablet Data (N/A)

Total Counter :	4330260	Tablets			
A.W.C Counter :	4275330	Tablets			
HEP :	5755 (0.1%)	Tablets	LEP :	8106 (0.2%)	Tablets
GOOD :	4261469 (99.7%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20 MG,STKQ1A00
User ID :	sj97904	Batch NO. :	KQM2501920
Print Interval :	50000 Tablets	Running Time :	19 Hour 03 Min 00 Sec
Total Counter :	4330260	Total Running Time :	1596 Hour 55 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	24	%	Manual ;	14	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		25	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.97	kN	No		
HEP :	30.0 %	16.97	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	13.32	kN	Yes 15	Times	
Ref :		13.05	kN			
LCP :	2.0 %	12.79	kN	Yes 15	Times	
LEP :	30.0 %	9.14	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.14	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.74	kN	Min :	1.17	kN	Punch NO.;	21
SD :	13.10	%	Max :	2.18	kN	Punch NO.;	54
Mean Main Pressure :	13.06	kN	Min :	9.64	kN	Punch NO.;	7
SD :	10.80	%	Max :	15.98	kN	Punch NO.;	39
Filling Depth :	Increase ;	1274	Times	Decrease ;	1271	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	30	RPM	Capacity :	234000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.05	mm	Pre Thickness ;	1.05	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.53	mm	Main Thickness ;	0.53	mm
Filling Depth :	6.42	mm	Current Cam :	Cam B	
Main Air pressure :	0.799	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	23	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.11	kN		
	Max ;	0.17	kN	Max Punch ;	11
Lower Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Ejection Force :	Average ;	0.13	kN		
	Max ;	0.23	kN	Max Punch ;	31

Tablet Data (N/A)

Total Counter :	4330260	Tablets			
A.W.C Counter :	4275330	Tablets			
HEP :	5755 (0.1%)	Tablets	LEP :	8106 (0.2%)	Tablets
GOOD :	4261469 (99.7%)	Tablets			