

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20 MG,STKQ1A00
User ID :	mr99799	Batch NO. :	KQM2502020
Print Interval :	50000 Tablets	Running Time :	18 Hour 59 Min 25 Sec
Total Counter :	4452830	Total Running Time :	1620 Hour 22 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	23	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		40	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.01	kN	No		
HEP :	30.0 %	18.01	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	14.13	kN	Yes 15	Times	
Ref :		13.85	kN			
LCP :	2.0 %	13.58	kN	Yes 15	Times	
LEP :	30.0 %	9.70	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.70	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.30	kN	Min :	1.74	kN	Punch NO.;	11
SD :	10.40	%	Max :	2.93	kN	Punch NO.;	50
Mean Main Pressure :	13.85	kN	Min :	11.57	kN	Punch NO.;	65
SD :	8.90	%	Max :	17.34	kN	Punch NO.;	34
Filling Depth :	Increase ;	2699	Times	Decrease ;	2954	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	30	RPM	Capacity :	234000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.05	mm	Pre Thickness ;	1.06	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.53	mm	Main Thickness ;	0.53	mm
Filling Depth :	6.47	mm	Current Cam :	Cam B	
Main Air pressure :	0.805	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	37	Min			
Lower Punch Remain Time (S2):	8	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.13	kN		
	Max ;	0.21	kN	Max Punch ;	31
Lower Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Ejection Force :	Average ;	0.14	kN		
	Max ;	0.25	kN	Max Punch ;	31

Tablet Data (N/A)

Total Counter :	4452830	Tablets			
A.W.C Counter :	4437298	Tablets			
HEP :	263 (0.0%)	Tablets	LEP :	1669 (0.0%)	Tablets
GOOD :	4435366 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20 MG,STKQ1A00
User ID :	mr99799	Batch NO. :	KQM2502020
Print Interval :	50000 Tablets	Running Time :	18 Hour 59 Min 25 Sec
Total Counter :	4452830	Total Running Time :	1620 Hour 22 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	27	%	Manual ;	14	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		40	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.90	kN	No		
HEP :	30.0 %	17.90	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	14.04	kN	Yes 15	Times	
Ref :		13.77	kN			
LCP :	2.0 %	13.49	kN	Yes 15	Times	
LEP :	30.0 %	9.64	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.64	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.79	kN	Min :	1.27	kN	Punch NO.;	13
SD :	12.70	%	Max :	2.26	kN	Punch NO.;	50
Mean Main Pressure :	13.85	kN	Min :	10.71	kN	Punch NO.;	60
SD :	9.30	%	Max :	16.50	kN	Punch NO.;	34
Filling Depth :	Increase ;	2054	Times	Decrease ;	2052	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	30	RPM	Capacity :	234000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.05	mm	Pre Thickness ;	1.05	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.53	mm	Main Thickness ;	0.53	mm
Filling Depth :	6.39	mm	Current Cam :	Cam B	
Main Air pressure :	0.805	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	37	Min			
Lower Punch Remain Time (S2):	8	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.13	kN		
	Max ;	0.21	kN	Max Punch ;	31
Lower Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Ejection Force :	Average ;	0.14	kN		
	Max ;	0.25	kN	Max Punch ;	31

Tablet Data (N/A)

Total Counter :	4452830	Tablets			
A.W.C Counter :	4437298	Tablets			
HEP :	263 (0.0%)	Tablets	LEP :	1669 (0.0%)	Tablets
GOOD :	4435366 (100.0%)	Tablets			