

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA100MG STSH4B00
User ID :	pb97604	Batch NO. :	SHM2502110
Print Interval :	50000 Tablets	Running Time :	02 Hour 54 Min 43 Sec
Total Counter :	750622	Total Running Time :	1627 Hour 57 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	26	%	Manual ;	20	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		3000000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		40	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.60	kN	No		
HEP :	30.0 %	18.60	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	14.59	kN	Yes 15	Times	
Ref :		14.31	kN			
LCP :	2.0 %	14.02	kN	Yes 15	Times	
LEP :	30.0 %	10.01	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	10.01	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.26	kN	Min :	1.20	kN	Punch NO.;	66
SD :	2.20	%	Max :	1.33	kN	Punch NO.;	5
Mean Main Pressure :	14.53	kN	Min :	13.49	kN	Punch NO.;	14
SD :	3.30	%	Max :	15.80	kN	Punch NO.;	5
Filling Depth :	Increase ; 54	Times	Decrease ;	117	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.58	mm	Pre Thickness ;	3.08	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.47	mm	Main Thickness ;	1.97	mm
Filling Depth :	9.62	mm	Current Cam :	Cam C	
Main Air pressure :	0.803	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	2	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.02	kN	Max Punch ;	40
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.12	kN	Max Punch ;	30
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.08	kN	Max Punch ;	51

Tablet Data (N/A)

Total Counter :	750622	Tablets			
A.W.C Counter :	738675	Tablets			
HEP :	6 (0.0%)	Tablets	LEP :	3 (0.0%)	Tablets
GOOD :	738666 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA100MG STSH4B00
User ID :	pb97604	Batch NO. :	SHM2502110
Print Interval :	50000 Tablets	Running Time :	02 Hour 54 Min 43 Sec
Total Counter :	750622	Total Running Time :	1627 Hour 57 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	25	%	Manual ;	14	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		40	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.66	kN	No		
HEP :	30.0 %	16.66	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	13.07	kN	Yes 15	Times	
Ref :		12.81	kN			
LCP :	2.0 %	12.56	kN	Yes 15	Times	
LEP :	30.0 %	8.97	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	8.97	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	0.86	kN	Min :	0.82	kN	Punch NO.;	62
SD :	2.70	%	Max :	0.92	kN	Punch NO.;	37
Mean Main Pressure :	12.96	kN	Min :	11.93	kN	Punch NO.;	27
SD :	4.30	%	Max :	14.77	kN	Punch NO.;	31
Filling Depth :	Increase ;	68	Times	Decrease ;	71	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.58	mm	Pre Thickness ;	3.08	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.50	mm	Main Thickness ;	2.00	mm
Filling Depth :	9.01	mm	Current Cam :	Cam C	
Main Air pressure :	0.803	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	2	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.04	kN	Max Punch ;	42
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.12	kN	Max Punch ;	30
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.08	kN	Max Punch ;	17

Tablet Data (N/A)

Total Counter :	750622	Tablets			
A.W.C Counter :	738675	Tablets			
HEP :	6 (0.0%)	Tablets	LEP :	3 (0.0%)	Tablets
GOOD :	738666 (100.0%)	Tablets			