

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA100MG STSH4B00
User ID :	pb97604	Batch NO. :	SHM2502210
Print Interval :	50000 Tablets	Running Time :	01 Hour 56 Min 06 Sec
Total Counter :	500346	Total Running Time :	1638 Hour 26 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	29	%	Manual ;	20	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		3000000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	1.8	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.22	kN	No		
HEP :	30.0 %	19.22	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	15.08	kN	Yes 15	Times	
Ref :		14.78	kN			
LCP :	2.0 %	14.49	kN	Yes 15	Times	
LEP :	30.0 %	10.35	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	10.35	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.34	kN	Min :	1.30	kN	Punch NO.;	58
SD :	1.40	%	Max :	1.39	kN	Punch NO.;	5
Mean Main Pressure :	14.68	kN	Min :	13.37	kN	Punch NO.;	11
SD :	3.30	%	Max :	16.31	kN	Punch NO.;	51
Filling Depth :	Increase ;	219	Times	Decrease ;	349	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.58	mm	Pre Thickness ;	3.08	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.47	mm	Main Thickness ;	1.97	mm
Filling Depth :	9.29	mm	Current Cam :	Cam C	
Main Air pressure :	0.818	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	13	Min			
Lower Punch Remain Time (S2):	10	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.04	kN	Max Punch ;	32
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.22	kN	Max Punch ;	44
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.08	kN	Max Punch ;	17

Tablet Data (N/A)

Total Counter :	500346	Tablets			
A.W.C Counter :	497497	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	497497 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA100MG STSH4B00
User ID :	pb97604	Batch NO. :	SHM2502210
Print Interval :	50000 Tablets	Running Time :	01 Hour 56 Min 06 Sec
Total Counter :	500346	Total Running Time :	1638 Hour 26 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	28	%	Manual ;	14	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	1.8	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.31	kN	No		
HEP :	30.0 %	17.31	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	13.58	kN	Yes 15	Times	
Ref :		13.32	kN			
LCP :	2.0 %	13.05	kN	Yes 15	Times	
LEP :	30.0 %	9.32	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.32	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	0.87	kN	Min :	0.82	kN	Punch NO.;	66
SD :	2.70	%	Max :	0.93	kN	Punch NO.;	1
Mean Main Pressure :	13.29	kN	Min :	12.03	kN	Punch NO.;	41
SD :	4.80	%	Max :	14.86	kN	Punch NO.;	59
Filling Depth :	Increase ;	281	Times	Decrease ;	273	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	3.00	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.50	mm	Main Thickness ;	2.00	mm
Filling Depth :	9.11	mm	Current Cam :	Cam C	
Main Air pressure :	0.818	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	13	Min			
Lower Punch Remain Time (S2):	10	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.04	kN	Max Punch ;	32
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.22	kN	Max Punch ;	44
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.08	kN	Max Punch ;	17

Tablet Data (N/A)

Total Counter :	500346	Tablets			
A.W.C Counter :	497497	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	497497 (100.0%)	Tablets			