

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA100MG STSH4B00
User ID :	sj97904	Batch NO. :	SHM2502210
Print Interval :	50000 Tablets	Running Time :	11 Hour 13 Min 14 Sec
Total Counter :	2902158	Total Running Time :	1647 Hour 44 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	29	%	Manual ;	20	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		3000000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.71	kN	No		
HEP :	30.0 %	19.71	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	15.47	kN	Yes 15	Times	
Ref :		15.16	kN			
LCP :	2.0 %	14.86	kN	Yes 15	Times	
LEP :	30.0 %	10.62	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	10.62	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	1.38	kN	Min :	1.36	kN	Punch NO.;	18
		1.10	%	Max :	1.42	kN	Punch NO.;	5
Mean Main Pressure :	SD :	15.09	kN	Min :	13.70	kN	Punch NO.;	42
		3.10	%	Max :	16.34	kN	Punch NO.;	64
Filling Depth :	Increase ;	407	Times	Decrease ;	520	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.58	mm	Pre Thickness ;	3.08	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.47	mm	Main Thickness ;	1.97	mm
Filling Depth :	9.74	mm	Current Cam :	Cam C	
Main Air pressure :	0.801	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	34	Min			
Lower Punch Remain Time (S2):	16	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.02	kN	Max Punch ;	42
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.11	kN	Max Punch ;	43
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.08	kN	Max Punch ;	17

Tablet Data (N/A)

Total Counter :	2902158	Tablets			
A.W.C Counter :	2897766	Tablets			
HEP :	0 (0%)	Tablets	LEP :	207 (0.0%)	Tablets
GOOD :	2897559 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA100MG STSH4B00
User ID :	sj97904	Batch NO. :	SHM2502210
Print Interval :	50000 Tablets	Running Time :	11 Hour 13 Min 14 Sec
Total Counter :	2902158	Total Running Time :	1647 Hour 44 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	28	%	Manual ;	14	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.30	kN	No		
HEP :	30.0 %	18.30	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	14.36	kN	Yes	15	Times
Ref :		14.08	kN			
LCP :	2.0 %	13.79	kN	Yes	15	Times
LEP :	30.0 %	9.85	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	9.85	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	0.95	kN	Min :	0.92	kN	Punch NO.;	44
SD :	1.90	%	Max :	1.00	kN	Punch NO.;	13
Mean Main Pressure :	14.24	kN	Min :	13.16	kN	Punch NO.;	26
SD :	4.90	%	Max :	16.51	kN	Punch NO.;	32
Filling Depth :	Increase ;	443	Times	Decrease ;	418	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	3.00	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.50	mm	Main Thickness ;	2.00	mm
Filling Depth :	9.46	mm	Current Cam :	Cam C	
Main Air pressure :	0.801	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	34	Min			
Lower Punch Remain Time (S2):	16	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.11	kN	Max Punch ;	43
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.08	kN	Max Punch ;	17

Tablet Data (N/A)

Total Counter :	2902158	Tablets			
A.W.C Counter :	2897766	Tablets			
HEP :	0 (0%)	Tablets	LEP :	207 (0.0%)	Tablets
GOOD :	2897559 (100.0%)	Tablets			