

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA100MG STSH4B00
User ID :	rp98927	Batch NO. :	SHM2502410
Print Interval :	50000 Tablets	Running Time :	05 Hour 13 Min 26 Sec
Total Counter :	1350810	Total Running Time :	1664 Hour 36 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	43	%	Manual ;	20	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		3000000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	20.10	kN	No		
HEP :	30.0 %	20.10	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	15.77	kN	Yes 15	Times	
Ref :		15.46	kN			
LCP :	2.0 %	15.15	kN	Yes 15	Times	
LEP :	30.0 %	10.82	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	10.82	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.46	kN	Min :	1.41	kN	Punch NO.;	62
SD :	1.40	%	Max :	1.50	kN	Punch NO.;	8
Mean Main Pressure :	15.14	kN	Min :	13.65	kN	Punch NO.;	47
SD :	2.90	%	Max :	16.31	kN	Punch NO.;	35
Filling Depth :	Increase ;	490	Times	Decrease ;	636	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.58	mm	Pre Thickness ;	3.08	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.54	mm	Main Thickness ;	2.04	mm
Filling Depth :	9.33	mm	Current Cam :	Cam C	
Main Air pressure :	0.796	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	53	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.05	kN	Max Punch ;	37
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.18	kN	Max Punch ;	44
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.06	kN	Max Punch ;	37

Tablet Data (N/A)

Total Counter :	1350810	Tablets			
A.W.C Counter :	1345998	Tablets			
HEP :	29 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1345969 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA100MG STSH4B00
User ID :	rp98927	Batch NO. :	SHM2502410
Print Interval :	50000 Tablets	Running Time :	05 Hour 13 Min 26 Sec
Total Counter :	1350810	Total Running Time :	1664 Hour 36 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	48	%	Manual ;	14	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.92	kN	No		
HEP :	30.0 %	17.92	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	14.06	kN	Yes 15	Times	
Ref :		13.78	kN			
LCP :	2.0 %	13.51	kN	Yes 15	Times	
LEP :	30.0 %	9.65	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.65	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.05	kN	Min :	1.01	kN	Punch NO.;	66
SD :	2.10	%	Max :	1.10	kN	Punch NO.;	37
Mean Main Pressure :	13.81	kN	Min :	13.05	kN	Punch NO.;	19
SD :	4.00	%	Max :	15.47	kN	Punch NO.;	32
Filling Depth :	Increase ;	673	Times	Decrease ;	864	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	13	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	3.00	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.68	mm	Main Thickness ;	2.18	mm
Filling Depth :	9.47	mm	Current Cam :	Cam C	
Main Air pressure :	0.796	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	53	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.05	kN	Max Punch ;	37
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.18	kN	Max Punch ;	44
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.06	kN	Max Punch ;	37

Tablet Data (N/A)

Total Counter :	1350810	Tablets			
A.W.C Counter :	1345998	Tablets			
HEP :	29 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1345969 (100.0%)	Tablets			