

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA100MG STSH4B00
User ID :	sj97904	Batch NO. :	SHM2502610
Print Interval :	50000 Tablets	Running Time :	11 Hour 14 Min 34 Sec
Total Counter :	2906846	Total Running Time :	1693 Hour 40 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	46	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	1.6	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.94	kN	No		
HEP :	30.0 %	19.94	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	15.65	kN	Yes 15	Times	
Ref :		15.34	kN			
LCP :	2.0 %	15.03	kN	Yes 15	Times	
LEP :	30.0 %	10.74	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	10.74	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.51	kN	Min :	1.45	kN	Punch NO.;	30
SD :	1.30	%	Max :	1.56	kN	Punch NO.;	5
Mean Main Pressure :	15.47	kN	Min :	14.43	kN	Punch NO.;	19
SD :	2.60	%	Max :	16.47	kN	Punch NO.;	32
Filling Depth :	Increase ; 1	Times	Decrease ;	0	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	13	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.58	mm	Pre Thickness ;	3.08	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.54	mm	Main Thickness ;	2.04	mm
Filling Depth :	9.50	mm	Current Cam :	Cam C	
Main Air pressure :	0.721	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	18	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.05	kN	Max Punch ;	31
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.12	kN	Max Punch ;	47
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.06	kN	Max Punch ;	37

Tablet Data (N/A)

Total Counter :	2906846	Tablets			
A.W.C Counter :	2902081	Tablets			
HEP :	6 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	2902075 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA100MG STSH4B00
User ID :	sj97904	Batch NO. :	SHM2502610
Print Interval :	50000 Tablets	Running Time :	11 Hour 14 Min 34 Sec
Total Counter :	2906846	Total Running Time :	1693 Hour 40 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	50	%	Manual ;	14	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	1.6	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.50	kN	No		
HEP :	30.0 %	17.50	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	13.73	kN	Yes	15	Times
Ref :		13.46	kN			
LCP :	2.0 %	13.20	kN	Yes	15	Times
LEP :	30.0 %	9.43	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	9.43	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.18	kN	Min :	1.15	kN	Punch NO.;	62
SD :	1.40	%	Max :	1.22	kN	Punch NO.;	47
Mean Main Pressure :	13.25	kN	Min :	12.51	kN	Punch NO.;	47
SD :	3.40	%	Max :	14.51	kN	Punch NO.;	32
Filling Depth :	Increase ;	27	Times	Decrease ;	25	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	3.00	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.67	mm	Main Thickness ;	2.17	mm
Filling Depth :	9.60	mm	Current Cam :	Cam C	
Main Air pressure :	0.721	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	18	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.05	kN	Max Punch ;	31
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.13	kN	Max Punch ;	30
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.06	kN	Max Punch ;	37

Tablet Data (N/A)

Total Counter :	2906846	Tablets			
A.W.C Counter :	2902081	Tablets			
HEP :	6 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	2902075 (100.0%)	Tablets			