

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20 MG,STKQ1A00
User ID :	sj97904	Batch NO. :	KQM2502120
Print Interval :	50000 Tablets	Running Time :	01 Hour 52 Min 58 Sec
Total Counter :	439306	Total Running Time :	1695 Hour 51 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	25	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		58	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	1.6	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.00	kN	No		
HEP :	25.0 %	16.35	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	13.34	kN	Yes 15	Times	
Ref :		13.08	kN			
LCP :	2.0 %	12.82	kN	Yes 15	Times	
LEP :	25.0 %	9.81	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.16	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.53	kN	Min :	2.20	kN	Punch NO.;	17
SD :	7.10	%	Max :	2.95	kN	Punch NO.;	9
Mean Main Pressure :	12.99	kN	Min :	10.65	kN	Punch NO.;	17
SD :	7.30	%	Max :	14.93	kN	Punch NO.;	9
Filling Depth :	Increase ; 188	Times	Decrease ;	179	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	30	RPM	Capacity :	234000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.35	mm	Pre Thickness ;	1.35	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.60	mm	Main Thickness ;	0.60	mm
Filling Depth :	6.63	mm	Current Cam :	Cam B	
Main Air pressure :	0.800	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	6	Min			
Lower Punch Remain Time (S2):	2	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.05	kN		
	Max ;	0.14	kN	Max Punch ;	51
Lower Punch :	Average ;	0.20	kN		
	Max ;	0.33	kN	Max Punch ;	22
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.12	kN	Max Punch ;	30

Tablet Data (N/A)

Total Counter :	439306	Tablets			
A.W.C Counter :	432001	Tablets			
HEP :	187 (0.0%)	Tablets	LEP :	108 (0.0%)	Tablets
GOOD :	431706 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20 MG,STKQ1A00
User ID :	sj97904	Batch NO. :	KQM2502120
Print Interval :	50000 Tablets	Running Time :	01 Hour 52 Min 59 Sec
Total Counter :	439368	Total Running Time :	1695 Hour 51 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	27	%	Manual ;	14	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		58	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	1.6	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.48	kN	No		
HEP :	25.0 %	16.81	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	13.72	kN	Yes 15	Times	
Ref :		13.45	kN			
LCP :	2.0 %	13.18	kN	Yes 15	Times	
LEP :	25.0 %	10.09	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.41	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.62	kN	Min :	2.09	kN	Punch NO.;	41
SD :	10.30	%	Max :	3.36	kN	Punch NO.;	57
Mean Main Pressure :	14.39	kN	Min :	11.64	kN	Punch NO.;	41
SD :	8.10	%	Max :	17.63	kN	Punch NO.;	57
Filling Depth :	Increase ;	183	Times	Decrease ;	189	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	30	RPM	Capacity :	234000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.26	mm	Pre Thickness ;	1.26	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.66	mm	Main Thickness ;	0.66	mm
Filling Depth :	6.52	mm	Current Cam :	Cam B	
Main Air pressure :	0.801	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	6	Min			
Lower Punch Remain Time (S2):	2	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.05	kN		
	Max ;	0.16	kN	Max Punch ;	64
Lower Punch :	Average ;	0.20	kN		
	Max ;	0.33	kN	Max Punch ;	22
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.12	kN	Max Punch ;	30

Tablet Data (N/A)

Total Counter :	439368	Tablets			
A.W.C Counter :	432066	Tablets			
HEP :	187 (0.0%)	Tablets	LEP :	108 (0.0%)	Tablets
GOOD :	431771 (99.9%)	Tablets			