

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20 MG,STKQ1A00
User ID :	sj97904	Batch NO. :	KQM2502120
Print Interval :	50000 Tablets	Running Time :	01 Hour 55 Min 13 Sec
Total Counter :	448042	Total Running Time :	1695 Hour 54 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	25	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		58	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	1.6	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.00	kN	No		
HEP :	25.0 %	16.35	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	13.34	kN	Yes	15	Times
Ref :		13.08	kN			
LCP :	2.0 %	12.82	kN	Yes	15	Times
LEP :	25.0 %	9.81	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	9.16	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.56	kN	Min :	2.09	kN	Punch NO.;	45
SD :	8.10	%	Max :	3.35	kN	Punch NO.;	29
Mean Main Pressure :	13.23	kN	Min :	10.90	kN	Punch NO.;	26
SD :	8.80	%	Max :	17.35	kN	Punch NO.;	29
Filling Depth :	Increase ;	189	Times	Decrease ;	189	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	30	RPM	Capacity :	234000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.35	mm	Pre Thickness ;	1.35	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.60	mm	Main Thickness ;	0.60	mm
Filling Depth :	6.36	mm	Current Cam :	Cam B	
Main Air pressure :	0.801	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	3	Min			
Lower Punch Remain Time (S2):	14	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.05	kN		
	Max ;	0.16	kN	Max Punch ;	57
Lower Punch :	Average ;	0.19	kN		
	Max ;	0.33	kN	Max Punch ;	21
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.17	kN	Max Punch ;	34

Tablet Data (N/A)

Total Counter :	448042	Tablets			
A.W.C Counter :	440711	Tablets			
HEP :	223 (0.1%)	Tablets	LEP :	116 (0.0%)	Tablets
GOOD :	440372 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20 MG,STKQ1A00
User ID :	sj97904	Batch NO. :	KQM2502120
Print Interval :	50000 Tablets	Running Time :	01 Hour 55 Min 13 Sec
Total Counter :	448042	Total Running Time :	1695 Hour 54 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	27	%	Manual ;	14	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		58	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	1.6	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.48	kN	No		
HEP :	25.0 %	16.81	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	13.72	kN	Yes	15	Times
Ref :		13.45	kN			
LCP :	2.0 %	13.18	kN	Yes	15	Times
LEP :	25.0 %	10.09	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	9.41	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.49	kN	Min :	2.00	kN	Punch NO.;	1
SD :	10.30	%	Max :	3.01	kN	Punch NO.;	53
Mean Main Pressure :	13.70	kN	Min :	11.24	kN	Punch NO.;	6
SD :	8.60	%	Max :	15.94	kN	Punch NO.;	35
Filling Depth :	Increase ;	192	Times	Decrease ;	199	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	30	RPM	Capacity :	234000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.26	mm	Pre Thickness ;	1.26	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.66	mm	Main Thickness ;	0.66	mm
Filling Depth :	6.49	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.801	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	3	Min			
Lower Punch Remain Time (S2):	14	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.05	kN		
	Max ;	0.18	kN	Max Punch ;	57
Lower Punch :	Average ;	0.19	kN		
	Max ;	0.33	kN	Max Punch ;	21
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.17	kN	Max Punch ;	34

Tablet Data (N/A)

Total Counter :	448042	Tablets			
A.W.C Counter :	440711	Tablets			
HEP :	223 (0.1%)	Tablets	LEP :	116 (0.0%)	Tablets
GOOD :	440372 (99.9%)	Tablets			