

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20 MG,STKQ1A00
User ID :	sj97904	Batch NO. :	KQM2502120
Print Interval :	50000 Tablets	Running Time :	02 Hour 02 Min 50 Sec
Total Counter :	477634	Total Running Time :	1696 Hour 1 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	25	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		58	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	1.6	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.00	kN	No		
HEP :	25.0 %	16.35	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	13.34	kN	Yes 15	Times	
Ref :		13.08	kN			
LCP :	2.0 %	12.82	kN	Yes 15	Times	
LEP :	25.0 %	9.81	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.16	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.42	kN	Min :	2.04	kN	Punch NO.;	28
SD :	6.30	%	Max :	2.77	kN	Punch NO.;	12
Mean Main Pressure :	12.41	kN	Min :	10.45	kN	Punch NO.;	28
SD :	6.70	%	Max :	14.25	kN	Punch NO.;	62
Filling Depth :	Increase ; 219	Times	Decrease ;	216	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	30	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.35	mm	Pre Thickness ;	1.35	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.60	mm	Main Thickness ;	0.60	mm
Filling Depth :	6.45	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.802	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	54	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.06	kN		
	Max ;	0.18	kN	Max Punch ;	57
Lower Punch :	Average ;	0.20	kN		
	Max ;	0.33	kN	Max Punch ;	38
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.16	kN	Max Punch ;	34

Tablet Data (N/A)

Total Counter :	477634	Tablets			
A.W.C Counter :	469632	Tablets			
HEP :	511 (0.1%)	Tablets	LEP :	138 (0.0%)	Tablets
GOOD :	468983 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20 MG,STKQ1A00
User ID :	sj97904	Batch NO. :	KQM2502120
Print Interval :	50000 Tablets	Running Time :	02 Hour 02 Min 51 Sec
Total Counter :	477698	Total Running Time :	1696 Hour 1 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	27	%	Manual ;	14	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		58	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	1.6	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.48	kN	No		
HEP :	25.0 %	16.81	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	13.72	kN	Yes	15	Times
Ref :		13.45	kN			
LCP :	2.0 %	13.18	kN	Yes	15	Times
LEP :	25.0 %	10.09	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	9.41	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.15	kN	Min :	1.41	kN	Punch NO.;	17
SD :	11.80	%	Max :	2.80	kN	Punch NO.;	51
Mean Main Pressure :	14.20	kN	Min :	9.26	kN	Punch NO.;	17
SD :	10.60	%	Max :	18.22	kN	Punch NO.;	51
Filling Depth :	Increase ;	212	Times	Decrease ;	232	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	30	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.36	mm	Pre Thickness ;	1.36	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.66	mm	Main Thickness ;	0.66	mm
Filling Depth :	6.13	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.802	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	54	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.05	kN		
	Max ;	0.18	kN	Max Punch ;	64
Lower Punch :	Average ;	0.20	kN		
	Max ;	0.33	kN	Max Punch ;	38
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.16	kN	Max Punch ;	34

Tablet Data (N/A)

Total Counter :	477698	Tablets			
A.W.C Counter :	469632	Tablets			
HEP :	511 (0.1%)	Tablets	LEP :	138 (0.0%)	Tablets
GOOD :	468983 (99.9%)	Tablets			