

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20 MG,STKQ1A00
User ID :	sj97904	Batch NO. :	KQM2502120
Print Interval :	50000 Tablets	Running Time :	02 Hour 27 Min 51 Sec
Total Counter :	564858	Total Running Time :	1696 Hour 26 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	25	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		58	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	1.6	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.28	kN	No		
HEP :	25.0 %	15.65	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	12.77	kN	Yes	15	Times
Ref :		12.52	kN			
LCP :	2.0 %	12.27	kN	Yes	15	Times
LEP :	25.0 %	9.39	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	8.77	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.85	kN	Min :	2.36	kN	Punch NO.;	17
SD :	5.70	%	Max :	3.19	kN	Punch NO.;	9
Mean Main Pressure :	12.68	kN	Min :	10.38	kN	Punch NO.;	17
SD :	5.30	%	Max :	14.40	kN	Punch NO.;	9
Filling Depth :	Increase ;	14	Times	Decrease ;	21	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	6	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.27	mm	Pre Thickness ;	1.28	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.60	mm	Main Thickness ;	0.60	mm
Filling Depth :	6.06	mm	Current Cam :	Cam B	
Main Air pressure :	0.807	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	32	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.06	kN		
	Max ;	0.14	kN	Max Punch ;	51
Lower Punch :	Average ;	0.18	kN		
	Max ;	0.28	kN	Max Punch ;	22
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.09	kN	Max Punch ;	62

Tablet Data (N/A)

Total Counter :	564858	Tablets			
A.W.C Counter :	554251	Tablets			
HEP :	1295 (0.2%)	Tablets	LEP :	578 (0.1%)	Tablets
GOOD :	552378 (99.7%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20 MG,STKQ1A00
User ID :	sj97904	Batch NO. :	KQM2502120
Print Interval :	50000 Tablets	Running Time :	02 Hour 27 Min 51 Sec
Total Counter :	564858	Total Running Time :	1696 Hour 26 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	29	%	Manual ;	14	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		58	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	1.6	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.15	kN	No		
HEP :	25.0 %	15.53	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	12.67	kN	Yes	15	Times
Ref :		12.42	kN			
LCP :	2.0 %	12.17	kN	Yes	15	Times
LEP :	25.0 %	9.32	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	8.69	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.90	kN	Min :	1.42	kN	Punch NO.;	17
SD :	7.60	%	Max :	2.21	kN	Punch NO.;	43
Mean Main Pressure :	12.34	kN	Min :	9.24	kN	Punch NO.;	17
SD :	6.40	%	Max :	14.11	kN	Punch NO.;	49
Filling Depth :	Increase ;	15	Times	Decrease ;	11	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.36	mm	Pre Thickness ;	1.36	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.66	mm	Main Thickness ;	0.67	mm
Filling Depth :	6.23	mm	Current Cam :	Cam B	
Main Air pressure :	0.807	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	32	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.06	kN		
	Max ;	0.14	kN	Max Punch ;	51
Lower Punch :	Average ;	0.17	kN		
	Max ;	0.28	kN	Max Punch ;	22
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.08	kN	Max Punch ;	62

Tablet Data (N/A)

Total Counter :	564858	Tablets			
A.W.C Counter :	554251	Tablets			
HEP :	1295 (0.2%)	Tablets	LEP :	578 (0.1%)	Tablets
GOOD :	552378 (99.7%)	Tablets			