

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20 MG,STKQ1A00
User ID :	sj97904	Batch NO. :	KQM2502120
Print Interval :	50000 Tablets	Running Time :	02 Hour 58 Min 35 Sec
Total Counter :	664874	Total Running Time :	1696 Hour 57 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	20	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		58	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	1.6	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.06	kN	No		
HEP :	25.0 %	15.45	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	12.60	kN	Yes 15	Times	
Ref :		12.36	kN			
LCP :	2.0 %	12.11	kN	Yes 15	Times	
LEP :	25.0 %	9.27	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	8.65	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.45	kN	Min :	1.94	kN	Punch NO.;	17
SD :	5.80	%	Max :	2.74	kN	Punch NO.;	9
Mean Main Pressure :	12.21	kN	Min :	9.47	kN	Punch NO.;	17
SD :	5.80	%	Max :	13.93	kN	Punch NO.;	57
Filling Depth :	Increase ; 46	Times	Decrease ; 53	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	5	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.35	mm	Pre Thickness ;	1.36	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.60	mm	Main Thickness ;	0.60	mm
Filling Depth :	6.05	mm	Current Cam :	Cam B	
Main Air pressure :	0.722	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	1	Min			
Lower Punch Remain Time (S2):	14	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.08	kN		
	Max ;	0.16	kN	Max Punch ;	51
Lower Punch :	Average ;	0.19	kN		
	Max ;	0.34	kN	Max Punch ;	36
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.08	kN	Max Punch ;	38

Tablet Data (N/A)

Total Counter :	664874	Tablets			
A.W.C Counter :	654286	Tablets			
HEP :	1298 (0.2%)	Tablets	LEP :	632 (0.1%)	Tablets
GOOD :	652356 (99.7%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20 MG,STKQ1A00
User ID :	sj97904	Batch NO. :	KQM2502120
Print Interval :	50000 Tablets	Running Time :	02 Hour 58 Min 35 Sec
Total Counter :	664874	Total Running Time :	1696 Hour 57 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	29	%	Manual ;	14	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		58	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	1.6	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.15	kN	No		
HEP :	25.0 %	15.53	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	12.67	kN	Yes	15	Times
Ref :		12.42	kN			
LCP :	2.0 %	12.17	kN	Yes	15	Times
LEP :	25.0 %	9.32	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	8.69	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.91	kN	Min :	1.56	kN	Punch NO.;	26
SD :	7.50	%	Max :	2.23	kN	Punch NO.;	39
Mean Main Pressure :	12.44	kN	Min :	10.23	kN	Punch NO.;	17
SD :	6.20	%	Max :	14.27	kN	Punch NO.;	57
Filling Depth :	Increase ;	36	Times	Decrease ;	33	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	4.36	mm	Pre Thickness ;	1.36	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.66	mm	Main Thickness ;	0.67	mm
Filling Depth :	6.20	mm	Current Cam :	Cam B	
Main Air pressure :	0.722	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	1	Min			
Lower Punch Remain Time (S2):	14	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.08	kN		
	Max ;	0.16	kN	Max Punch ;	51
Lower Punch :	Average ;	0.19	kN		
	Max ;	0.34	kN	Max Punch ;	36
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.08	kN	Max Punch ;	38

Tablet Data (N/A)

Total Counter :	664874	Tablets			
A.W.C Counter :	654286	Tablets			
HEP :	1298 (0.2%)	Tablets	LEP :	632 (0.1%)	Tablets
GOOD :	652356 (99.7%)	Tablets			