

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20 MG,STKQ1A00
User ID :	sj97904	Batch NO. :	KQM2502120
Print Interval :	50000 Tablets	Running Time :	03 Hour 26 Min 10 Sec
Total Counter :	5445436	Total Running Time :	1721 Hour 28 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	17	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		40	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.01	kN	No		
HEP :	25.0 %	16.35	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	13.34	kN	Yes	15	Times
Ref :		13.08	kN			
LCP :	2.0 %	12.82	kN	Yes	15	Times
LEP :	25.0 %	9.81	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	9.16	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.92	kN	Min :	1.33	kN	Punch NO.;	43
SD :	15.70	%	Max :	2.82	kN	Punch NO.;	24
Mean Main Pressure :	14.52	kN	Min :	11.34	kN	Punch NO.;	43
SD :	11.30	%	Max :	18.68	kN	Punch NO.;	24
Filling Depth :	Increase ;	368	Times	Decrease ;	359	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	4	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.36	mm	Pre Thickness ;	1.37	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.60	mm	Main Thickness ;	0.61	mm
Filling Depth :	6.71	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.718	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	4	Min			
Lower Punch Remain Time (S2):	2	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	On	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.07	kN		
	Max ;	0.19	kN	Max Punch ;	61
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.15	kN	Max Punch ;	20
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.06	kN	Max Punch ;	55

Tablet Data (N/A)

Total Counter :	5445436	Tablets			
A.W.C Counter :	5423582	Tablets			
HEP :	1877 (0.0%)	Tablets	LEP :	1909 (0.0%)	Tablets
GOOD :	5419796 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20 MG,STKQ1A00
User ID :	sj97904	Batch NO. :	KQM2502120
Print Interval :	50000 Tablets	Running Time :	03 Hour 26 Min 10 Sec
Total Counter :	5445436	Total Running Time :	1721 Hour 28 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	20	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		40	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.04	kN	No		
HEP :	25.0 %	16.38	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	13.37	kN	Yes 15	Times	
Ref :		13.11	kN			
LCP :	2.0 %	12.84	kN	Yes 15	Times	
LEP :	25.0 %	9.83	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.17	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.07	kN	Min :	0.90	kN	Punch NO.;	38
SD :	13.70	%	Max :	1.56	kN	Punch NO.;	62
Mean Main Pressure :	8.24	kN	Min :	6.43	kN	Punch NO.;	17
SD :	15.10	%	Max :	12.50	kN	Punch NO.;	65
Filling Depth :	Increase ;	564	Times	Decrease ;	488	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	5	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.36	mm	Pre Thickness ;	1.37	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.66	mm	Main Thickness ;	0.67	mm
Filling Depth :	6.63	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.718	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	4	Min			
Lower Punch Remain Time (S2):	2	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	On	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.07	kN		
	Max ;	0.19	kN	Max Punch ;	61
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.17	kN	Max Punch ;	54
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.06	kN	Max Punch ;	54

Tablet Data (N/A)

Total Counter :	5445436	Tablets			
A.W.C Counter :	5423582	Tablets			
HEP :	1877 (0.0%)	Tablets	LEP :	1909 (0.0%)	Tablets
GOOD :	5419796 (99.9%)	Tablets			