

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20 MG,STKQ1A00
User ID :	rp98927	Batch NO. :	KQM2502220
Print Interval :	50000 Tablets	Running Time :	03 Hour 34 Min 59 Sec
Total Counter :	700426	Total Running Time :	1725 Hour 4 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	17	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		40	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.91	kN	No		
HEP :	25.0 %	16.26	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	13.27	kN	Yes	15	Times
Ref :		13.01	kN			
LCP :	2.0 %	12.75	kN	Yes	15	Times
LEP :	25.0 %	9.76	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	9.10	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.78	kN	Min :	1.45	kN	Punch NO.;	38
SD :	7.70	%	Max :	2.16	kN	Punch NO.;	7
Mean Main Pressure :	13.20	kN	Min :	11.35	kN	Punch NO.;	38
SD :	5.70	%	Max :	14.93	kN	Punch NO.;	7
Filling Depth :	Increase ;	474	Times	Decrease ;	476	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	4	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.36	mm	Pre Thickness ;	1.37	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.60	mm	Main Thickness ;	0.61	mm
Filling Depth :	6.21	mm	Current Cam :	Cam B	
Main Air pressure :	0.741	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	32	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.08	kN		
	Max ;	0.15	kN	Max Punch ;	12
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.26	kN	Max Punch ;	38
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.06	kN	Max Punch ;	27

Tablet Data (N/A)

Total Counter :	700426	Tablets			
A.W.C Counter :	691942	Tablets			
HEP :	86 (0.0%)	Tablets	LEP :	67 (0.0%)	Tablets
GOOD :	691789 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20 MG,STKQ1A00
User ID :	rp98927	Batch NO. :	KQM2502220
Print Interval :	50000 Tablets	Running Time :	03 Hour 34 Min 59 Sec
Total Counter :	700426	Total Running Time :	1725 Hour 4 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	16	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		40	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.04	kN	No		
HEP :	25.0 %	16.38	kN	Yes	10 Rotations	15 Tablets
HCP :	2.0 %	13.37	kN	Yes	15 Times	
Ref :		13.11	kN			
LCP :	2.0 %	12.84	kN	Yes	15 Times	
LEP :	25.0 %	9.83	kN	Yes	10 Rotations	15 Tablets
LSP :	30.0 %	9.17	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.84	kN	Min :	1.52	kN	Punch NO.;	17
SD :	8.00	%	Max :	2.15	kN	Punch NO.;	35
Mean Main Pressure :	12.96	kN	Min :	10.64	kN	Punch NO.;	17
SD :	6.90	%	Max :	14.92	kN	Punch NO.;	35
Filling Depth :	Increase ;	650	Times	Decrease ;	584	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	4	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.36	mm	Pre Thickness ;	1.37	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.66	mm	Main Thickness ;	0.67	mm
Filling Depth :	6.48	mm	Current Cam :	Cam B	
Main Air pressure :	0.741	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	32	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.08	kN		
	Max ;	0.15	kN	Max Punch ;	12
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.26	kN	Max Punch ;	38
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.06	kN	Max Punch ;	35

Tablet Data (N/A)

Total Counter :	700426	Tablets			
A.W.C Counter :	691942	Tablets			
HEP :	86 (0.0%)	Tablets	LEP :	67 (0.0%)	Tablets
GOOD :	691789 (100.0%)	Tablets			