

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20 MG,STKQ1A00
User ID :	pb97604	Batch NO. :	KQM2502220
Print Interval :	50000 Tablets	Running Time :	05 Hour 37 Min 43 Sec
Total Counter :	1100642	Total Running Time :	1727 Hour 7 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	17	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		40	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.91	kN	No		
HEP :	25.0 %	16.26	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	13.27	kN	Yes 15	Times	
Ref :		13.01	kN			
LCP :	2.0 %	12.75	kN	Yes 15	Times	
LEP :	25.0 %	9.76	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.10	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	1.76	kN	Min :	1.40	kN	Punch NO.;	17
		9.10	%	Max :	2.18	kN	Punch NO.;	58
Mean Main Pressure :	SD :	12.99	kN	Min :	10.94	kN	Punch NO.;	17
		6.30	%	Max :	15.11	kN	Punch NO.;	57
Filling Depth :	Increase ;	676	Times	Decrease ;	676	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	4	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.36	mm	Pre Thickness ;	1.37	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.60	mm	Main Thickness ;	0.61	mm
Filling Depth :	6.19	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.753	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	32	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.14	kN		
	Max ;	0.19	kN	Max Punch ;	57
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.25	kN	Max Punch ;	37
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.04	kN	Max Punch ;	55

Tablet Data (N/A)

Total Counter :	1100642	Tablets			
A.W.C Counter :	1091149	Tablets			
HEP :	134 (0.0%)	Tablets	LEP :	109 (0.0%)	Tablets
GOOD :	1090906 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20 MG,STKQ1A00
User ID :	pb97604	Batch NO. :	KQM2502220
Print Interval :	50000 Tablets	Running Time :	05 Hour 37 Min 43 Sec
Total Counter :	1100642	Total Running Time :	1727 Hour 7 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	16	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		40	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.04	kN	No		
HEP :	25.0 %	16.38	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	13.37	kN	Yes 15	Times	
Ref :		13.11	kN			
LCP :	2.0 %	12.84	kN	Yes 15	Times	
LEP :	25.0 %	9.83	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.17	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	1.68	kN	Min :	1.33	kN	Punch NO.;	26
		8.00	%	Max :	1.99	kN	Punch NO.;	58
Mean Main Pressure :		13.29	kN	Min :	10.82	kN	Punch NO.;	17
	SD :	6.70	%	Max :	15.01	kN	Punch NO.;	57
Filling Depth :	Increase ;	699	Times	Decrease ;	637	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	4	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.36	mm	Pre Thickness ;	1.37	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.60	mm	Main Thickness ;	0.61	mm
Filling Depth :	6.36	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.753	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	32	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.14	kN		
	Max ;	0.20	kN	Max Punch ;	1
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.25	kN	Max Punch ;	37
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.04	kN	Max Punch ;	55

Tablet Data (N/A)

Total Counter :	1100642	Tablets			
A.W.C Counter :	1091149	Tablets			
HEP :	134 (0.0%)	Tablets	LEP :	109 (0.0%)	Tablets
GOOD :	1090906 (100.0%)	Tablets			