

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20 MG,STKQ1A00
User ID :	rp98927	Batch NO. :	KQM2502220
Print Interval :	50000 Tablets	Running Time :	22 Hour 30 Min 30 Sec
Total Counter :	4402300	Total Running Time :	1744 Hour 2 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	20	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		40	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.01	kN	No		
HEP :	25.0 %	16.36	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	13.35	kN	Yes 15	Times	
Ref :		13.08	kN			
LCP :	2.0 %	12.82	kN	Yes 15	Times	
LEP :	25.0 %	9.81	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.16	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.67	kN	Min :	1.39	kN	Punch NO.;	12
SD :	7.70	%	Max :	1.93	kN	Punch NO.;	55
Mean Main Pressure :	13.09	kN	Min :	11.59	kN	Punch NO.;	17
SD :	5.40	%	Max :	14.56	kN	Punch NO.;	55
Filling Depth :	Increase ;	1434	Times	Decrease ;	1469	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	5	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.34	mm	Pre Thickness ;	1.35	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.57	mm	Main Thickness ;	0.58	mm
Filling Depth :	6.05	mm	Current Cam :	Cam B	
Main Air pressure :	0.789	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	20	Min			
Lower Punch Remain Time (S2):	10	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.15	kN		
	Max ;	0.21	kN	Max Punch ;	32
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.26	kN	Max Punch ;	38
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.07	kN	Max Punch ;	27

Tablet Data (N/A)

Total Counter :	4402300	Tablets			
A.W.C Counter :	4390779	Tablets			
HEP :	528 (0.0%)	Tablets	LEP :	570 (0.0%)	Tablets
GOOD :	4389681 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20 MG,STKQ1A00
User ID :	rp98927	Batch NO. :	KQM2502220
Print Interval :	50000 Tablets	Running Time :	22 Hour 30 Min 30 Sec
Total Counter :	4402300	Total Running Time :	1744 Hour 2 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	20	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		40	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.16	kN	No		
HEP :	25.0 %	16.50	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	13.47	kN	Yes 15	Times	
Ref :		13.20	kN			
LCP :	2.0 %	12.94	kN	Yes 15	Times	
LEP :	25.0 %	9.90	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.24	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.79	kN	Min :	1.50	kN	Punch NO.;	6
SD :	6.60	%	Max :	2.05	kN	Punch NO.;	55
Mean Main Pressure :	12.97	kN	Min :	11.41	kN	Punch NO.;	17
SD :	5.60	%	Max :	14.65	kN	Punch NO.;	57
Filling Depth :	Increase ;	1031	Times	Decrease ;	980	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	195000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	5	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.34	mm	Pre Thickness ;	1.35	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.63	mm	Main Thickness ;	0.64	mm
Filling Depth :	6.41	mm	Current Cam :	Cam B	
Main Air pressure :	0.789	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	20	Min			
Lower Punch Remain Time (S2):	10	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.15	kN		
	Max ;	0.20	kN	Max Punch ;	12
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.26	kN	Max Punch ;	38
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.07	kN	Max Punch ;	27

Tablet Data (N/A)

Total Counter :	4402300	Tablets			
A.W.C Counter :	4390779	Tablets			
HEP :	528 (0.0%)	Tablets	LEP :	570 (0.0%)	Tablets
GOOD :	4389681 (100.0%)	Tablets			