

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Amio 200mg STAI3A00
User ID :	sj97904	Batch NO. :	AIM2500420
Print Interval :	50000 Tablets	Running Time :	04 Hour 35 Min 59 Sec
Total Counter :	409770	Total Running Time :	1753 Hour 52 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	124	%	Manual ;	20	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	26.52	kN	No		
HEP :	25.0 %	25.50	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	20.81	kN	Yes 15	Times	
Ref :		20.40	kN			
LCP :	2.0 %	19.99	kN	Yes 15	Times	
LEP :	25.0 %	15.30	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	14.28	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	3.03	kN	Min :	2.30	kN	Punch NO.;	49
		11.00	%	Max :	4.06	kN	Punch NO.;	53
Mean Main Pressure :		19.80	kN	Min :	17.28	kN	Punch NO.;	49
	SD :	5.30	%	Max :	23.39	kN	Punch NO.;	53
Filling Depth :	Increase ;	47	Times	Decrease ;	57	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	19	RPM
Pre Upper Punch Position ;	2.20	mm			
Pre Lower Punch Position ;	3.40	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	2.80	mm			
Main Lower Punch Position ;	3.40	mm	Main Thickness ;	0.60	mm
Filling Depth :	6.44	mm	Current Cam :	Cam B	
Main Air pressure :	0.804	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	50	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.12	kN		
	Max ;	0.20	kN	Max Punch ;	13
Lower Punch :	Average ;	0.16	kN		
	Max ;	0.35	kN	Max Punch ;	1
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.04	kN	Max Punch ;	4

Tablet Data (N/A)

Total Counter :	409770	Tablets			
A.W.C Counter :	406888	Tablets			
HEP :	375 (0.1%)	Tablets	LEP :	156 (0.0%)	Tablets
GOOD :	406357 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Amio 200mg STAI3A00
User ID :	sj97904	Batch NO. :	AIM2500420
Print Interval :	50000 Tablets	Running Time :	04 Hour 36 Min 00 Sec
Total Counter :	409796	Total Running Time :	1753 Hour 52 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	124	%	Manual ;	20	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	28.29	kN	No		
HEP :	25.0 %	27.21	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	22.20	kN	Yes 15	Times	
Ref :		21.76	kN			
LCP :	2.0 %	21.33	kN	Yes 15	Times	
LEP :	25.0 %	16.32	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	15.23	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	2.78	kN	Min :	2.12	kN	Punch NO.;	4
		9.60	%	Max :	3.30	kN	Punch NO.;	2
Mean Main Pressure :		20.83	kN	Min :	19.15	kN	Punch NO.;	33
	SD :	4.10	%	Max :	22.87	kN	Punch NO.;	27
Filling Depth :	Increase ;	31	Times	Decrease ;	33	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	19	RPM
Pre Upper Punch Position ;	2.20	mm			
Pre Lower Punch Position ;	3.40	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	2.80	mm			
Main Lower Punch Position ;	3.40	mm	Main Thickness ;	0.60	mm
Filling Depth :	6.99	mm	Current Cam :	Cam B	
Main Air pressure :	0.804	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	50	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.12	kN		
	Max ;	0.20	kN	Max Punch ;	13
Lower Punch :	Average ;	0.17	kN		
	Max ;	0.39	kN	Max Punch ;	1
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.04	kN	Max Punch ;	4

Tablet Data (N/A)

Total Counter :	409796	Tablets			
A.W.C Counter :	406888	Tablets			
HEP :	375 (0.1%)	Tablets	LEP :	156 (0.0%)	Tablets
GOOD :	406357 (99.9%)	Tablets			