

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Amio 200mg STAI3A00
User ID :	pb97604	Batch NO. :	AIM2500420
Print Interval :	50000 Tablets	Running Time :	15 Hour 21 Min 44 Sec
Total Counter :	1429800	Total Running Time :	1764 Hour 39 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	122	%	Manual ;	20	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	26.00	kN	No		
HEP :	25.0 %	25.00	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	20.40	kN	Yes 15	Times	
Ref :		20.00	kN			
LCP :	2.0 %	19.60	kN	Yes 15	Times	
LEP :	25.0 %	15.00	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	14.00	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.46	kN	Min :	2.89	kN	Punch NO.;	29
SD :	8.90	%	Max :	4.32	kN	Punch NO.;	2
Mean Main Pressure :	17.99	kN	Min :	16.57	kN	Punch NO.;	33
SD :	4.30	%	Max :	20.11	kN	Punch NO.;	2
Filling Depth :	Increase ;	1200	Times	Decrease ;	1199	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.20	mm			
Pre Lower Punch Position ;	3.35	mm	Pre Thickness ;	1.15	mm
Main Upper Punch Position ;	2.80	mm			
Main Lower Punch Position ;	3.48	mm	Main Thickness ;	0.68	mm
Filling Depth :	7.44	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.797	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	6	Min			
Lower Punch Remain Time (S2):	37	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.10	kN		
	Max ;	0.16	kN	Max Punch ;	10
Lower Punch :	Average ;	0.21	kN		
	Max ;	0.23	kN	Max Punch ;	3
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.05	kN	Max Punch ;	42

Tablet Data (N/A)

Total Counter :	1429800	Tablets			
A.W.C Counter :	1426722	Tablets			
HEP :	885 (0.1%)	Tablets	LEP :	406 (0.0%)	Tablets
GOOD :	1425431 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Amio 200mg STAI3A00
User ID :	pb97604	Batch NO. :	AIM2500420
Print Interval :	50000 Tablets	Running Time :	15 Hour 21 Min 44 Sec
Total Counter :	1429800	Total Running Time :	1764 Hour 39 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	124	%	Manual ;	20	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	29.54	kN	No		
HEP :	25.0 %	28.41	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	23.18	kN	Yes 15	Times	
Ref :		22.72	kN			
LCP :	2.0 %	22.27	kN	Yes 15	Times	
LEP :	25.0 %	17.04	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	15.91	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.07	kN	Min :	2.32	kN	Punch NO.;	33
SD :	11.60	%	Max :	4.00	kN	Punch NO.;	53
Mean Main Pressure :	21.93	kN	Min :	18.92	kN	Punch NO.;	33
SD :	5.50	%	Max :	24.69	kN	Punch NO.;	53
Filling Depth :	Increase ;	559	Times	Decrease ;	568	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	19	RPM
Pre Upper Punch Position ;	2.20	mm			
Pre Lower Punch Position ;	3.40	mm	Pre Thickness ;	1.20	mm
Main Upper Punch Position ;	2.80	mm			
Main Lower Punch Position ;	3.42	mm	Main Thickness ;	0.62	mm
Filling Depth :	6.88	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.797	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	6	Min			
Lower Punch Remain Time (S2):	37	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.10	kN		
	Max ;	0.15	kN	Max Punch ;	10
Lower Punch :	Average ;	0.21	kN		
	Max ;	0.23	kN	Max Punch ;	3
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.05	kN	Max Punch ;	42

Tablet Data (N/A)

Total Counter :	1429800	Tablets			
A.W.C Counter :	1426722	Tablets			
HEP :	885 (0.1%)	Tablets	LEP :	406 (0.0%)	Tablets
GOOD :	1425431 (99.9%)	Tablets			