

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	GLICLAZIDE MR 30MG
User ID :	pb97604	Batch NO. :	GLC TAB XV 25 003
Print Interval :	50000 Tablets	Running Time :	00 Hour 11 Min 50 Sec
Total Counter :	18830	Total Running Time :	1764 Hour 50 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	90	%	Manual ;	20	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	13.79	kN	No		
HEP :	25.0 %	13.26	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	10.82	kN	Yes 15	Times	
Ref :		10.61	kN			
LCP :	2.0 %	10.39	kN	Yes 15	Times	
LEP :	25.0 %	7.96	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	7.42	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.49	kN	Min :	1.36	kN	Punch NO.;	8
SD :	4.30	%	Max :	1.64	kN	Punch NO.;	26
Mean Main Pressure :	10.85	kN	Min :	10.26	kN	Punch NO.;	2
SD :	2.60	%	Max :	11.50	kN	Punch NO.;	26
Filling Depth :	Increase ; 5	Times	Decrease ; 11	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.32	mm	Pre Thickness ;	2.33	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.47	mm	Main Thickness ;	1.48	mm
Filling Depth :	5.10	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.808	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	6	Min			
Lower Punch Remain Time (S2):	37	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.08	kN		
	Max ;	0.15	kN	Max Punch ;	4
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.11	kN	Max Punch ;	51
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.04	kN	Max Punch ;	41

Tablet Data (N/A)

Total Counter :	18830	Tablets			
A.W.C Counter :	10154	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	10154 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	GLICLAZIDE MR 30MG
User ID :	pb97604	Batch NO. :	GLC TAB XV 25 003
Print Interval :	50000 Tablets	Running Time :	00 Hour 11 Min 51 Sec
Total Counter :	18856	Total Running Time :	1764 Hour 50 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	90	%	Manual ;	24	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	12.41	kN	No		
HEP :	25.0 %	11.93	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	9.74	kN	Yes 15	Times	
Ref :		9.54	kN			
LCP :	2.0 %	9.35	kN	Yes 15	Times	
LEP :	25.0 %	7.16	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	6.68	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.04	kN	Min :	0.94	kN	Punch NO.;	53
SD :	4.10	%	Max :	1.15	kN	Punch NO.;	46
Mean Main Pressure :	9.67	kN	Min :	9.17	kN	Punch NO.;	48
SD :	3.00	%	Max :	10.51	kN	Punch NO.;	46
Filling Depth :	Increase ; 4	Times	Decrease ; 5	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.49	mm	Pre Thickness ;	2.50	mm
Main Upper Punch Position ;	2.98	mm			
Main Lower Punch Position ;	4.56	mm	Main Thickness ;	1.58	mm
Filling Depth :	5.55	mm	Current Cam :	Cam B	
Main Air pressure :	0.807	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	6	Min			
Lower Punch Remain Time (S2):	37	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.07	kN		
	Max ;	0.15	kN	Max Punch ;	36
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.11	kN	Max Punch ;	51
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.04	kN	Max Punch ;	41

Tablet Data (N/A)

Total Counter :	18856	Tablets			
A.W.C Counter :	10154	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	10154 (100.0%)	Tablets			