

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	GLICLAZIDE MR 30MG
User ID :	rp98927	Batch NO. :	GLC TAB XV 25 003
Print Interval :	50000 Tablets	Running Time :	01 Hour 52 Min 07 Sec
Total Counter :	256938	Total Running Time :	1766 Hour 31 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	71	%	Manual ;	20	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	15.06	kN	No		
HEP :	25.0 %	14.49	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	11.82	kN	Yes 15	Times	
Ref :		11.59	kN			
LCP :	2.0 %	11.36	kN	Yes 15	Times	
LEP :	25.0 %	8.69	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	8.11	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.43	kN	Min :	1.28	kN	Punch NO.;	9
SD :	3.90	%	Max :	1.55	kN	Punch NO.;	42
Mean Main Pressure :	11.50	kN	Min :	10.43	kN	Punch NO.;	27
SD :	3.40	%	Max :	12.39	kN	Punch NO.;	42
Filling Depth :	Increase ; 20	Times	Decrease ; 48	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.32	mm	Pre Thickness ;	2.33	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.41	mm	Main Thickness ;	1.42	mm
Filling Depth :	5.47	mm	Current Cam :	Cam B	
Main Air pressure :	0.768	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	1	Min			
Lower Punch Remain Time (S2):	12	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.03	kN	Max Punch ;	43
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.13	kN	Max Punch ;	26
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.04	kN	Max Punch ;	3

Tablet Data (N/A)

Total Counter :	256938	Tablets			
A.W.C Counter :	247043	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	247043 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	GLICLAZIDE MR 30MG
User ID :	rp98927	Batch NO. :	GLC TAB XV 25 003
Print Interval :	50000 Tablets	Running Time :	01 Hour 52 Min 07 Sec
Total Counter :	256938	Total Running Time :	1766 Hour 31 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	71	%	Manual ;	24	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	13.74	kN	No		
HEP :	25.0 %	13.21	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	10.78	kN	Yes 15	Times	
Ref :		10.57	kN			
LCP :	2.0 %	10.36	kN	Yes 15	Times	
LEP :	25.0 %	7.93	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	7.40	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	1.33	kN	Min :	1.19	kN	Punch NO.;	12
		4.60	%	Max :	1.45	kN	Punch NO.;	3
Mean Main Pressure :	SD :	10.64	kN	Min :	9.79	kN	Punch NO.;	12
		3.30	%	Max :	11.35	kN	Punch NO.;	52
Filling Depth :	Increase ;	26	Times	Decrease ;	26	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.40	mm	Pre Thickness ;	2.41	mm
Main Upper Punch Position ;	2.98	mm			
Main Lower Punch Position ;	4.56	mm	Main Thickness ;	1.58	mm
Filling Depth :	5.95	mm	Current Cam :	Cam B	
Main Air pressure :	0.768	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	1	Min			
Lower Punch Remain Time (S2):	12	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.03	kN	Max Punch ;	43
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.15	kN	Max Punch ;	26
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.04	kN	Max Punch ;	13

Tablet Data (N/A)

Total Counter :	256938	Tablets			
A.W.C Counter :	247043	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	247043 (100.0%)	Tablets			