

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	GLICLAZIDE MR 30MG
User ID :	yu98249	Batch NO. :	GLC TAB XV 25 003
Print Interval :	50000 Tablets	Running Time :	07 Hour 46 Min 15 Sec
Total Counter :	1107294	Total Running Time :	1772 Hour 26 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	78	%	Manual ;	20	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	14.07	kN	No		
HEP :	25.0 %	13.53	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	11.04	kN	Yes 15	Times	
Ref :		10.82	kN			
LCP :	2.0 %	10.61	kN	Yes 15	Times	
LEP :	25.0 %	8.12	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	7.58	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.31	kN	Min :	1.16	kN	Punch NO.;	9
SD :	3.90	%	Max :	1.41	kN	Punch NO.;	44
Mean Main Pressure :	10.65	kN	Min :	9.72	kN	Punch NO.;	9
SD :	3.10	%	Max :	11.42	kN	Punch NO.;	17
Filling Depth :	Increase ; 34	Times	Decrease ;	80	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	16	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.32	mm	Pre Thickness ;	2.33	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.47	mm	Main Thickness ;	1.48	mm
Filling Depth :	5.20	mm	Current Cam :	Cam B	
Main Air pressure :	0.780	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	8	Min			
Lower Punch Remain Time (S2):	19	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.14	kN	Max Punch ;	46
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.06	kN	Max Punch ;	42

Tablet Data (N/A)

Total Counter :	1107294	Tablets			
A.W.C Counter :	1096037	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1096037 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	GLICLAZIDE MR 30MG
User ID :	yu98249	Batch NO. :	GLC TAB XV 25 003
Print Interval :	50000 Tablets	Running Time :	07 Hour 46 Min 15 Sec
Total Counter :	1107294	Total Running Time :	1772 Hour 26 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	78	%	Manual ;	24	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	14.13	kN	No		
HEP :	25.0 %	13.59	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	11.09	kN	Yes 15	Times	
Ref :		10.87	kN			
LCP :	2.0 %	10.66	kN	Yes 15	Times	
LEP :	25.0 %	8.15	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	7.61	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.23	kN	Min :	1.08	kN	Punch NO.;	40
SD :	4.70	%	Max :	1.43	kN	Punch NO.;	7
Mean Main Pressure :	10.89	kN	Min :	10.06	kN	Punch NO.;	33
SD :	4.30	%	Max :	12.29	kN	Punch NO.;	7
Filling Depth :	Increase ; 46	Times	Decrease ; 55	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	16	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.40	mm	Pre Thickness ;	2.41	mm
Main Upper Punch Position ;	2.98	mm			
Main Lower Punch Position ;	4.55	mm	Main Thickness ;	1.57	mm
Filling Depth :	5.61	mm	Current Cam :	Cam B	
Main Air pressure :	0.780	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	8	Min			
Lower Punch Remain Time (S2):	19	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.14	kN	Max Punch ;	12
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.06	kN	Max Punch ;	42

Tablet Data (N/A)

Total Counter :	1107294	Tablets			
A.W.C Counter :	1096037	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1096037 (100.0%)	Tablets			