

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	GLICLAZIDE MR 30MG
User ID :	yu98249	Batch NO. :	GLC TAB XV 25 003
Print Interval :	50000 Tablets	Running Time :	09 Hour 44 Min 06 Sec
Total Counter :	1357384	Total Running Time :	1774 Hour 24 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	78	%	Manual ;	20	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	14.08	kN	No		
HEP :	25.0 %	13.54	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	11.04	kN	Yes 15	Times	
Ref :		10.83	kN			
LCP :	2.0 %	10.61	kN	Yes 15	Times	
LEP :	25.0 %	8.12	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	7.58	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	1.24	kN	Min :	1.14	kN	Punch NO.;	47
		3.80	%	Max :	1.35	kN	Punch NO.;	7
Mean Main Pressure :		10.52	kN	Min :	9.97	kN	Punch NO.;	1
	SD :	2.70	%	Max :	11.17	kN	Punch NO.;	7
Filling Depth :	Increase ;	57	Times	Decrease ;	103	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	16	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.32	mm	Pre Thickness ;	2.33	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.47	mm	Main Thickness ;	1.48	mm
Filling Depth :	5.40	mm	Current Cam :	Cam B	
Main Air pressure :	0.803	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	11	Min			
Lower Punch Remain Time (S2):	22	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	35
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.15	kN	Max Punch ;	32
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.08	kN	Max Punch ;	6

Tablet Data (N/A)

Total Counter :	1357384	Tablets			
A.W.C Counter :	1345935	Tablets			
HEP :	61 (0.0%)	Tablets	LEP :	36 (0.0%)	Tablets
GOOD :	1345838 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	GLICLAZIDE MR 30MG
User ID :	yu98249	Batch NO. :	GLC TAB XV 25 003
Print Interval :	50000 Tablets	Running Time :	09 Hour 44 Min 06 Sec
Total Counter :	1357384	Total Running Time :	1774 Hour 24 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	78	%	Manual ;	24	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	14.13	kN	No		
HEP :	25.0 %	13.59	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	11.09	kN	Yes 15	Times	
Ref :		10.87	kN			
LCP :	2.0 %	10.66	kN	Yes 15	Times	
LEP :	25.0 %	8.15	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	7.61	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.21	kN	Min :	1.10	kN	Punch NO.;	14
SD :	5.20	%	Max :	1.35	kN	Punch NO.;	51
Mean Main Pressure :	10.84	kN	Min :	10.01	kN	Punch NO.;	14
SD :	4.40	%	Max :	11.85	kN	Punch NO.;	51
Filling Depth :	Increase ; 82	Times	Decrease ; 67	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	16	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.40	mm	Pre Thickness ;	2.41	mm
Main Upper Punch Position ;	2.98	mm			
Main Lower Punch Position ;	4.55	mm	Main Thickness ;	1.57	mm
Filling Depth :	5.68	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.803	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	11	Min			
Lower Punch Remain Time (S2):	22	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.01	kN	Max Punch ;	35
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.15	kN	Max Punch ;	32
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.08	kN	Max Punch ;	6

Tablet Data (N/A)

Total Counter :	1357384	Tablets			
A.W.C Counter :	1345935	Tablets			
HEP :	61 (0.0%)	Tablets	LEP :	36 (0.0%)	Tablets
GOOD :	1345838 (100.0%)	Tablets			