

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20MG STKQ1A00
User ID :	kp99540	Batch NO. :	KQM2502320
Print Interval :	50000 Tablets	Running Time :	03 Hour 14 Min 32 Sec
Total Counter :	750554	Total Running Time :	1778 Hour 26 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	12	%	Manual ;	10	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	13.62	kN	No		
HEP :	25.0 %	13.09	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	10.68	kN	Yes	15	Times
Ref :		10.48	kN			
LCP :	2.0 %	10.27	kN	Yes	15	Times
LEP :	25.0 %	7.86	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	7.33	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.08	kN	Min :	2.04	kN	Punch NO.;	51
SD :	0.80	%	Max :	2.13	kN	Punch NO.;	30
Mean Main Pressure :	10.47	kN	Min :	9.24	kN	Punch NO.;	60
SD :	3.00	%	Max :	11.09	kN	Punch NO.;	55
Filling Depth :	Increase ;	21	Times	Decrease ;	24	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	30	RPM	Capacity :	234000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	4	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.20	mm	Pre Thickness ;	2.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.72	mm	Main Thickness ;	0.72	mm
Filling Depth :	6.46	mm	Current Cam :	Cam B	
Main Air pressure :	0.796	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	17	Min			
Lower Punch Remain Time (S2):	28	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.34	kN		
	Max ;	0.42	kN	Max Punch ;	9
Lower Punch :	Average ;	0.16	kN		
	Max ;	0.26	kN	Max Punch ;	41
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.11	kN	Max Punch ;	41

Tablet Data (N/A)

Total Counter :	750554	Tablets			
A.W.C Counter :	738498	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	738498 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20MG STKQ1A00
User ID :	kp99540	Batch NO. :	KQM2502320
Print Interval :	50000 Tablets	Running Time :	03 Hour 14 Min 32 Sec
Total Counter :	750554	Total Running Time :	1778 Hour 26 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	14	%	Manual ;	10	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	13.29	kN	No		
HEP :	25.0 %	12.78	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	10.43	kN	Yes	15	Times
Ref :		10.22	kN			
LCP :	2.0 %	10.02	kN	Yes	15	Times
LEP :	25.0 %	7.67	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	7.16	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.00	kN	Min :	1.97	kN	Punch NO.;	10
SD :	0.80	%	Max :	2.05	kN	Punch NO.;	37
Mean Main Pressure :	10.10	kN	Min :	8.90	kN	Punch NO.;	60
SD :	3.10	%	Max :	10.75	kN	Punch NO.;	40
Filling Depth :	Increase ;	4	Times	Decrease ;	4	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	30	RPM	Capacity :	234000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	4	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.20	mm	Pre Thickness ;	2.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.82	mm	Main Thickness ;	0.82	mm
Filling Depth :	6.52	mm	Current Cam :	Cam B	
Main Air pressure :	0.796	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	17	Min			
Lower Punch Remain Time (S2):	28	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.34	kN		
	Max ;	0.40	kN	Max Punch ;	38
Lower Punch :	Average ;	0.16	kN		
	Max ;	0.26	kN	Max Punch ;	41
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.11	kN	Max Punch ;	41

Tablet Data (N/A)

Total Counter :	750554	Tablets			
A.W.C Counter :	738498	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	738498 (100.0%)	Tablets			