

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20MG STKQ1A00
User ID :	ks99394	Batch NO. :	KQM2502320
Print Interval :	50000 Tablets	Running Time :	15 Hour 46 Min 03 Sec
Total Counter :	3691838	Total Running Time :	1790 Hour 58 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	12	%	Manual ;	10	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	15.57	kN	No		
HEP :	25.0 %	14.97	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	12.21	kN	Yes	15	Times
Ref :		11.97	kN			
LCP :	2.0 %	11.73	kN	Yes	15	Times
LEP :	25.0 %	8.98	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	8.38	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.91	kN	Min :	1.82	kN	Punch NO.;	42
SD :	1.60	%	Max :	1.98	kN	Punch NO.;	48
Mean Main Pressure :	11.88	kN	Min :	10.08	kN	Punch NO.;	60
SD :	4.10	%	Max :	12.78	kN	Punch NO.;	7
Filling Depth :	Increase ;	10	Times	Decrease ;	8	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	30	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	4	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.20	mm	Pre Thickness ;	2.21	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.60	mm	Main Thickness ;	0.60	mm
Filling Depth :	6.53	mm	Current Cam :	Cam B	
Main Air pressure :	0.800	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	4	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.18	kN		
	Max ;	0.25	kN	Max Punch ;	47
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.27	kN	Max Punch ;	36
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.08	kN	Max Punch ;	36

Tablet Data (N/A)

Total Counter :	3691838	Tablets			
A.W.C Counter :	3675111	Tablets			
HEP :	198 (0.0%)	Tablets	LEP :	892 (0.0%)	Tablets
GOOD :	3674021 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20MG STKQ1A00
User ID :	ks99394	Batch NO. :	KQM2502320
Print Interval :	50000 Tablets	Running Time :	15 Hour 46 Min 03 Sec
Total Counter :	3691838	Total Running Time :	1790 Hour 58 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	14	%	Manual ;	10	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	14.07	kN	No		
HEP :	25.0 %	13.53	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	11.04	kN	Yes	15	Times
Ref :		10.83	kN			
LCP :	2.0 %	10.61	kN	Yes	15	Times
LEP :	25.0 %	8.12	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	7.58	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.91	kN	Min :	1.85	kN	Punch NO.;	8
SD :	1.80	%	Max :	2.00	kN	Punch NO.;	51
Mean Main Pressure :	10.97	kN	Min :	9.43	kN	Punch NO.;	60
SD :	4.30	%	Max :	11.85	kN	Punch NO.;	11
Filling Depth :	Increase ;	5	Times	Decrease ;	2	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	30	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	4	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.20	mm	Pre Thickness ;	2.21	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.78	mm	Main Thickness ;	0.79	mm
Filling Depth :	6.73	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.800	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	4	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.17	kN		
	Max ;	0.24	kN	Max Punch ;	47
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.27	kN	Max Punch ;	36
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.08	kN	Max Punch ;	36

Tablet Data (N/A)

Total Counter :	3691838	Tablets			
A.W.C Counter :	3675176	Tablets			
HEP :	198 (0.0%)	Tablets	LEP :	892 (0.0%)	Tablets
GOOD :	3674086 (100.0%)	Tablets			