

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20MG STKQ1A00
User ID :	yu98249	Batch NO. :	KQM2502320
Print Interval :	50000 Tablets	Running Time :	21 Hour 18 Min 15 Sec
Total Counter :	4992740	Total Running Time :	1796 Hour 31 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	12	%	Manual ;	10	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	14.91	kN	No		
HEP :	25.0 %	14.34	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	11.70	kN	Yes 15	Times	
Ref :		11.47	kN			
LCP :	2.0 %	11.24	kN	Yes 15	Times	
LEP :	25.0 %	8.60	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	8.03	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.97	kN	Min :	1.89	kN	Punch NO.;	52
SD :	1.30	%	Max :	2.05	kN	Punch NO.;	8
Mean Main Pressure :	11.50	kN	Min :	9.62	kN	Punch NO.;	60
SD :	4.00	%	Max :	12.44	kN	Punch NO.;	48
Filling Depth :	Increase ;	152	Times	Decrease ;	127	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	30	RPM	Capacity :	234000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	4	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.20	mm	Pre Thickness ;	2.21	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.60	mm	Main Thickness ;	0.60	mm
Filling Depth :	6.84	mm	Current Cam :	Cam B	
Main Air pressure :	0.806	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	4	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.18	kN		
	Max ;	0.25	kN	Max Punch ;	47
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.22	kN	Max Punch ;	52
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.06	kN	Max Punch ;	40

Tablet Data (N/A)

Total Counter :	4992740	Tablets			
A.W.C Counter :	4975070	Tablets			
HEP :	204 (0.0%)	Tablets	LEP :	892 (0.0%)	Tablets
GOOD :	4973974 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 20MG STKQ1A00
User ID :	yu98249	Batch NO. :	KQM2502320
Print Interval :	50000 Tablets	Running Time :	21 Hour 18 Min 15 Sec
Total Counter :	4992740	Total Running Time :	1796 Hour 31 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	14	%	Manual ;	10	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		5500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	14.07	kN	No		
HEP :	25.0 %	13.53	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	11.04	kN	Yes	15	Times
Ref :		10.83	kN			
LCP :	2.0 %	10.61	kN	Yes	15	Times
LEP :	25.0 %	8.12	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	7.58	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	1.93	kN	Min :	1.88	kN	Punch NO.;	18
		1.20	%	Max :	2.00	kN	Punch NO.;	14
Mean Main Pressure :		10.67	kN	Min :	9.47	kN	Punch NO.;	60
	SD :	3.60	%	Max :	11.96	kN	Punch NO.;	14
Filling Depth :	Increase ;	38	Times	Decrease ;	36	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	30	RPM	Capacity :	234000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	4	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.20	mm	Pre Thickness ;	2.21	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.78	mm	Main Thickness ;	0.79	mm
Filling Depth :	6.72	mm	Current Cam :	Cam B	
Main Air pressure :	0.806	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	4	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.18	kN		
	Max ;	0.25	kN	Max Punch ;	47
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.22	kN	Max Punch ;	52
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.06	kN	Max Punch ;	26

Tablet Data (N/A)

Total Counter :	4992740	Tablets			
A.W.C Counter :	4975070	Tablets			
HEP :	204 (0.0%)	Tablets	LEP :	892 (0.0%)	Tablets
GOOD :	4973974 (100.0%)	Tablets			