

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG STKQ1B00
User ID :	os190259	Batch NO. :	KQM2507440
Print Interval :	50000 Tablets	Running Time :	00 Hour 23 Min 43 Sec
Total Counter :	61776	Total Running Time :	1798 Hour 33 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	55	%	Manual ;	10	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		35	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	34.82	kN	No		
HEP :	25.0 %	33.48	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	27.32	kN	Yes 15	Times	
Ref :		26.79	kN			
LCP :	2.0 %	26.25	kN	Yes 15	Times	
LEP :	25.0 %	20.09	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	18.75	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.22	kN	Min :	1.15	kN	Punch NO.;	33
SD :	2.30	%	Max :	1.29	kN	Punch NO.;	50
Mean Main Pressure :	26.95	kN	Min :	24.34	kN	Punch NO.;	33
SD :	3.80	%	Max :	29.82	kN	Punch NO.;	50
Filling Depth :	Increase ; 1	Times	Decrease ;	14	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	171600	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.00	mm	Pre Thickness ;	2.01	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.95	mm	Main Thickness ;	0.95	mm
Filling Depth :	4.85	mm	Current Cam :	Cam B	
Main Air pressure :	0.796	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	24	Min			
Lower Punch Remain Time (S2):	10	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.05	kN	Max Punch ;	58
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.14	kN	Max Punch ;	64
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.05	kN	Max Punch ;	14

Tablet Data (N/A)

Total Counter :	61776	Tablets			
A.W.C Counter :	44154	Tablets			
HEP :	0 (0%)	Tablets	LEP :	90 (0.2%)	Tablets
GOOD :	44064 (99.8%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG STKQ1B00
User ID :	os190259	Batch NO. :	KQM2507440
Print Interval :	50000 Tablets	Running Time :	00 Hour 23 Min 43 Sec
Total Counter :	61776	Total Running Time :	1798 Hour 33 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	55	%	Manual ;	10	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		35	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	33.13	kN	No		
HEP :	25.0 %	31.86	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	25.99	kN	Yes	15	Times
Ref :		25.48	kN			
LCP :	2.0 %	24.97	kN	Yes	15	Times
LEP :	25.0 %	19.11	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	17.84	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.16	kN	Min :	1.11	kN	Punch NO.;	18
SD :	2.10	%	Max :	1.24	kN	Punch NO.;	19
Mean Main Pressure :	25.64	kN	Min :	24.11	kN	Punch NO.;	54
SD :	3.40	%	Max :	28.11	kN	Punch NO.;	19
Filling Depth :	Increase ;	0	Times	Decrease ;	1	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	171600	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.00	mm	Pre Thickness ;	2.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.10	mm	Main Thickness ;	1.10	mm
Filling Depth :	4.28	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.796	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	24	Min			
Lower Punch Remain Time (S2):	10	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.05	kN	Max Punch ;	58
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.14	kN	Max Punch ;	64
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.05	kN	Max Punch ;	14

Tablet Data (N/A)

Total Counter :	61776	Tablets			
A.W.C Counter :	44154	Tablets			
HEP :	0 (0%)	Tablets	LEP :	90 (0.2%)	Tablets
GOOD :	44064 (99.8%)	Tablets			