

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG STKQ1B00
User ID :	os190259	Batch NO. :	KQM2507440
Print Interval :	50000 Tablets	Running Time :	01 Hour 33 Min 48 Sec
Total Counter :	261802	Total Running Time :	1799 Hour 43 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	55	%	Manual ;	10	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		35	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	34.82	kN	No		
HEP :	25.0 %	33.48	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	27.32	kN	Yes 15	Times	
Ref :		26.79	kN			
LCP :	2.0 %	26.25	kN	Yes 15	Times	
LEP :	25.0 %	20.09	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	18.75	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.20	kN	Min :	1.13	kN	Punch NO.;	25
SD :	2.30	%	Max :	1.26	kN	Punch NO.;	50
Mean Main Pressure :	26.62	kN	Min :	24.58	kN	Punch NO.;	24
SD :	3.60	%	Max :	28.94	kN	Punch NO.;	50
Filling Depth :	Increase ; 11	Times	Decrease ; 15	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	171600	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.00	mm	Pre Thickness ;	2.01	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.95	mm	Main Thickness ;	0.95	mm
Filling Depth :	5.12	mm	Current Cam :	Cam B	
Main Air pressure :	0.800	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	24	Min			
Lower Punch Remain Time (S2):	10	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.10	kN	Max Punch ;	32
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.20	kN	Max Punch ;	54
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.05	kN	Max Punch ;	34

Tablet Data (N/A)

Total Counter :	261802	Tablets			
A.W.C Counter :	244159	Tablets			
HEP :	0 (0%)	Tablets	LEP :	90 (0.0%)	Tablets
GOOD :	244069 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG STKQ1B00
User ID :	os190259	Batch NO. :	KQM2507440
Print Interval :	50000 Tablets	Running Time :	01 Hour 33 Min 48 Sec
Total Counter :	261802	Total Running Time :	1799 Hour 43 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	55	%	Manual ;	10	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		35	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	34.09	kN	No		
HEP :	25.0 %	32.78	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	26.75	kN	Yes	15	Times
Ref :		26.22	kN			
LCP :	2.0 %	25.70	kN	Yes	15	Times
LEP :	25.0 %	19.67	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	18.36	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.17	kN	Min :	1.13	kN	Punch NO.;	21
SD :	2.10	%	Max :	1.25	kN	Punch NO.;	42
Mean Main Pressure :	26.21	kN	Min :	24.64	kN	Punch NO.;	8
SD :	3.00	%	Max :	28.73	kN	Punch NO.;	43
Filling Depth :	Increase ;	2	Times	Decrease ;	6	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	171600	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.00	mm	Pre Thickness ;	2.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.10	mm	Main Thickness ;	1.10	mm
Filling Depth :	4.32	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.800	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	24	Min			
Lower Punch Remain Time (S2):	10	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.08	kN	Max Punch ;	13
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.20	kN	Max Punch ;	54
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.05	kN	Max Punch ;	34

Tablet Data (N/A)

Total Counter :	261802	Tablets			
A.W.C Counter :	244159	Tablets			
HEP :	0 (0%)	Tablets	LEP :	90 (0.0%)	Tablets
GOOD :	244069 (100.0%)	Tablets			