

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG STKQ1B00
User ID :	rp98927	Batch NO. :	KQM2507440
Print Interval :	50000 Tablets	Running Time :	05 Hour 56 Min 32 Sec
Total Counter :	1012126	Total Running Time :	1804 Hour 6 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	55	%	Manual ;	10	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	36.45	kN	No		
HEP :	25.0 %	35.05	kN	Yes	10 Rotations	15 Tablets
HCP :	2.0 %	28.60	kN	Yes	15 Times	
Ref :		28.04	kN			
LCP :	2.0 %	27.48	kN	Yes	15 Times	
LEP :	25.0 %	21.03	kN	Yes	10 Rotations	15 Tablets
LSP :	30.0 %	19.63	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.22	kN	Min :	1.12	kN	Punch NO.;	18
SD :	2.50	%	Max :	1.28	kN	Punch NO.;	42
Mean Main Pressure :	28.39	kN	Min :	25.20	kN	Punch NO.;	18
SD :	4.00	%	Max :	31.14	kN	Punch NO.;	43
Filling Depth :	Increase ;	59	Times	Decrease ;	51	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	171600	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.00	mm	Pre Thickness ;	2.01	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.95	mm	Main Thickness ;	0.95	mm
Filling Depth :	5.24	mm	Current Cam :	Cam B	
Main Air pressure :	0.789	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	4	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.15	kN		
	Max ;	0.36	kN	Max Punch ;	16
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.15	kN	Max Punch ;	33
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.04	kN	Max Punch ;	54

Tablet Data (N/A)

Total Counter :	1012126	Tablets			
A.W.C Counter :	985836	Tablets			
HEP :	158 (0.0%)	Tablets	LEP :	643 (0.1%)	Tablets
GOOD :	985035 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG STKQ1B00
User ID :	rp98927	Batch NO. :	KQM2507440
Print Interval :	50000 Tablets	Running Time :	05 Hour 56 Min 32 Sec
Total Counter :	1012126	Total Running Time :	1804 Hour 6 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	55	%	Manual ;	10	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	35.46	kN	No		
HEP :	25.0 %	34.10	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	27.83	kN	Yes	15	Times
Ref :		27.28	kN			
LCP :	2.0 %	26.73	kN	Yes	15	Times
LEP :	25.0 %	20.46	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	19.10	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.18	kN	Min :	1.12	kN	Punch NO.;	41
SD :	2.40	%	Max :	1.24	kN	Punch NO.;	17
Mean Main Pressure :	27.23	kN	Min :	25.02	kN	Punch NO.;	63
SD :	3.40	%	Max :	29.99	kN	Punch NO.;	17
Filling Depth :	Increase ;	20	Times	Decrease ;	34	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	171600	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.00	mm	Pre Thickness ;	2.00	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.10	mm	Main Thickness ;	1.11	mm
Filling Depth :	4.43	mm	Current Cam :	Cam B	
Main Air pressure :	0.789	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	4	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.15	kN		
	Max ;	0.39	kN	Max Punch ;	16
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.15	kN	Max Punch ;	33
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.04	kN	Max Punch ;	54

Tablet Data (N/A)

Total Counter :	1012126	Tablets			
A.W.C Counter :	985836	Tablets			
HEP :	158 (0.0%)	Tablets	LEP :	643 (0.1%)	Tablets
GOOD :	985035 (99.9%)	Tablets			