

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG STKQ1B00
User ID :	sj97904	Batch NO. :	KQM2507440
Print Interval :	50000 Tablets	Running Time :	14 Hour 07 Min 00 Sec
Total Counter :	2412876	Total Running Time :	1812 Hour 17 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	68	%	Manual ;	10	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	36.95	kN	No		
HEP :	25.0 %	35.53	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	28.99	kN	Yes	15	Times
Ref :		28.42	kN			
LCP :	2.0 %	27.85	kN	Yes	15	Times
LEP :	25.0 %	21.32	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	19.90	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.17	kN	Min :	1.10	kN	Punch NO.;	28
SD :	2.70	%	Max :	1.27	kN	Punch NO.;	17
Mean Main Pressure :	28.77	kN	Min :	25.78	kN	Punch NO.;	40
SD :	4.20	%	Max :	32.42	kN	Punch NO.;	17
Filling Depth :	Increase ;	69	Times	Decrease ;	98	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	171600	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.00	mm	Pre Thickness ;	2.01	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.95	mm	Main Thickness ;	0.95	mm
Filling Depth :	4.82	mm	Current Cam :	Cam B	
Main Air pressure :	0.795	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	74	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.09	kN		
	Max ;	0.27	kN	Max Punch ;	16
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.14	kN	Max Punch ;	33
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.04	kN	Max Punch ;	35

Tablet Data (N/A)

Total Counter :	2412876	Tablets			
A.W.C Counter :	2385742	Tablets			
HEP :	159 (0.0%)	Tablets	LEP :	643 (0.0%)	Tablets
GOOD :	2384940 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG STKQ1B00
User ID :	sj97904	Batch NO. :	KQM2507440
Print Interval :	50000 Tablets	Running Time :	14 Hour 07 Min 00 Sec
Total Counter :	2412876	Total Running Time :	1812 Hour 17 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	58	%	Manual ;	10	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	36.74	kN	No		
HEP :	25.0 %	35.33	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	28.83	kN	Yes	15	Times
Ref :		28.26	kN			
LCP :	2.0 %	27.70	kN	Yes	15	Times
LEP :	25.0 %	21.20	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	19.79	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.15	kN	Min :	1.09	kN	Punch NO.;	57
SD :	2.50	%	Max :	1.22	kN	Punch NO.;	43
Mean Main Pressure :	28.39	kN	Min :	26.57	kN	Punch NO.;	56
SD :	3.20	%	Max :	31.03	kN	Punch NO.;	50
Filling Depth :	Increase ;	40	Times	Decrease ;	75	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	171600	Tablets/hour
Feeder : Status ;	Auto		Speed ;	13	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.00	mm	Pre Thickness ;	2.00	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.10	mm	Main Thickness ;	1.11	mm
Filling Depth :	4.46	mm	Current Cam :	Cam B	
Main Air pressure :	0.795	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	74	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.09	kN		
	Max ;	0.27	kN	Max Punch ;	16
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.14	kN	Max Punch ;	55
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.04	kN	Max Punch ;	35

Tablet Data (N/A)

Total Counter :	2412876	Tablets			
A.W.C Counter :	2385742	Tablets			
HEP :	159 (0.0%)	Tablets	LEP :	643 (0.0%)	Tablets
GOOD :	2384940 (100.0%)	Tablets			