

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG STKQ1B00
User ID :	rp98927	Batch NO. :	KQM2507540
Print Interval :	50000 Tablets	Running Time :	02 Hour 37 Min 52 Sec
Total Counter :	450268	Total Running Time :	1816 Hour 49 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	68	%	Manual ;	10	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	37.35	kN	No		
HEP :	25.0 %	35.91	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	29.31	kN	Yes	15	Times
Ref :		28.73	kN			
LCP :	2.0 %	28.16	kN	Yes	15	Times
LEP :	25.0 %	21.55	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	20.11	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	1.12	kN	Min :	1.07	kN	Punch NO.;	12
		2.30	%	Max :	1.20	kN	Punch NO.;	17
Mean Main Pressure :	SD :	28.62	kN	Min :	26.26	kN	Punch NO.;	63
		3.70	%	Max :	31.81	kN	Punch NO.;	17
Filling Depth :	Increase ;	9	Times	Decrease ;	11	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	171600	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.00	mm	Pre Thickness ;	2.01	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	3.91	mm	Main Thickness ;	0.91	mm
Filling Depth :	4.64	mm	Current Cam :	Cam B	
Main Air pressure :	0.797	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	29	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.24	kN		
	Max ;	0.54	kN	Max Punch ;	19
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.13	kN	Max Punch ;	21
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.04	kN	Max Punch ;	59

Tablet Data (N/A)

Total Counter :	450268	Tablets			
A.W.C Counter :	447503	Tablets			
HEP :	53 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	447450 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO 40 MG STKQ1B00
User ID :	rp98927	Batch NO. :	KQM2507540
Print Interval :	50000 Tablets	Running Time :	02 Hour 37 Min 52 Sec
Total Counter :	450268	Total Running Time :	1816 Hour 49 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	58	%	Manual ;	10	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		2750000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	37.70	kN	No		
HEP :	25.0 %	36.25	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	29.58	kN	Yes	15	Times
Ref :		29.00	kN			
LCP :	2.0 %	28.42	kN	Yes	15	Times
LEP :	25.0 %	21.75	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	20.30	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.11	kN	Min :	1.05	kN	Punch NO.;	24
SD :	2.60	%	Max :	1.18	kN	Punch NO.;	21
Mean Main Pressure :	29.08	kN	Min :	26.60	kN	Punch NO.;	63
SD :	3.40	%	Max :	31.19	kN	Punch NO.;	50
Filling Depth :	Increase ;	31	Times	Decrease ;	21	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	171600	Tablets/hour
Feeder : Status ;	Auto		Speed ;	13	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.00	mm	Pre Thickness ;	2.00	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.05	mm	Main Thickness ;	1.06	mm
Filling Depth :	4.32	mm	Current Cam :	Cam B	
Main Air pressure :	0.797	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	29	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.24	kN		
	Max ;	0.54	kN	Max Punch ;	19
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.13	kN	Max Punch ;	21
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.04	kN	Max Punch ;	1

Tablet Data (N/A)

Total Counter :	450268	Tablets			
A.W.C Counter :	447503	Tablets			
HEP :	53 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	447450 (100.0%)	Tablets			