

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO40mgSTKQ1B00
User ID :	os190259	Batch NO. :	KQM2507640
Print Interval :	50000 Tablets	Running Time :	01 Hour 45 Min 40 Sec
Total Counter :	302000	Total Running Time :	1831 Hour 56 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	27	%	Manual ;	10	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	35.72	kN	No		
HEP :	25.0 %	34.35	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	28.03	kN	Yes 15	Times	
Ref :		27.48	kN			
LCP :	2.0 %	26.93	kN	Yes 15	Times	
LEP :	25.0 %	20.61	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	19.23	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.39	kN	Min :	1.30	kN	Punch NO.;	12
SD :	3.90	%	Max :	1.54	kN	Punch NO.;	49
Mean Main Pressure :	27.88	kN	Min :	26.11	kN	Punch NO.;	18
SD :	3.60	%	Max :	30.27	kN	Punch NO.;	43
Filling Depth :	Increase ; 72	Times	Decrease ;	119	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	171600	Tablets/hour
Feeder : Status ;	Auto		Speed ;	6	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	4.30	mm	Pre Thickness ;	1.80	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	3.50	mm	Main Thickness ;	1.00	mm
Filling Depth :	4.79	mm	Current Cam :	Cam B	
Main Air pressure :	0.833	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	19	Min			
Lower Punch Remain Time (S2):	17	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.09	kN		
	Max ;	0.16	kN	Max Punch ;	13
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.12	kN	Max Punch ;	16
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.04	kN	Max Punch ;	56

Tablet Data (N/A)

Total Counter :	302000	Tablets			
A.W.C Counter :	300193	Tablets			
HEP :	0 (0%)	Tablets	LEP :	88 (0.0%)	Tablets
GOOD :	300105 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO40mgSTKQ1B00
User ID :	os190259	Batch NO. :	KQM2507640
Print Interval :	50000 Tablets	Running Time :	01 Hour 45 Min 40 Sec
Total Counter :	302000	Total Running Time :	1831 Hour 56 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	38	%	Manual ;	10	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	37.63	kN	No		
HEP :	25.0 %	36.19	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	29.53	kN	Yes 15	Times	
Ref :		28.95	kN			
LCP :	2.0 %	28.37	kN	Yes 15	Times	
LEP :	25.0 %	21.71	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	20.26	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.30	kN	Min :	1.21	kN	Punch NO.;	45
SD :	3.70	%	Max :	1.42	kN	Punch NO.;	36
Mean Main Pressure :	29.01	kN	Min :	27.27	kN	Punch NO.;	12
SD :	3.60	%	Max :	31.47	kN	Punch NO.;	49
Filling Depth :	Increase ; 154	Times	Decrease ;	158	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	171600	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	4.30	mm	Pre Thickness ;	1.80	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	3.57	mm	Main Thickness ;	1.07	mm
Filling Depth :	4.46	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.833	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	19	Min			
Lower Punch Remain Time (S2):	17	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.09	kN		
	Max ;	0.16	kN	Max Punch ;	13
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.12	kN	Max Punch ;	16
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.04	kN	Max Punch ;	7

Tablet Data (N/A)

Total Counter :	302000	Tablets			
A.W.C Counter :	300193	Tablets			
HEP :	0 (0%)	Tablets	LEP :	88 (0.0%)	Tablets
GOOD :	300105 (100.0%)	Tablets			