

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO40mgSTKQ1B00
User ID :	rp98927	Batch NO. :	KQM2507840
Print Interval :	50000 Tablets	Running Time :	00 Hour 11 Min 46 Sec
Total Counter :	31324	Total Running Time :	1862 Hour 21 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	29	%	Manual ;	30	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	32.48	kN	No		
HEP :	25.0 %	31.23	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	25.48	kN	Yes 15	Times	
Ref :		24.98	kN			
LCP :	2.0 %	24.48	kN	Yes 15	Times	
LEP :	25.0 %	18.74	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	17.49	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.06	kN	Min :	1.02	kN	Punch NO.;	11
SD :	1.70	%	Max :	1.10	kN	Punch NO.;	30
Mean Main Pressure :	25.27	kN	Min :	23.71	kN	Punch NO.;	51
SD :	3.60	%	Max :	27.21	kN	Punch NO.;	44
Filling Depth :	Increase ; 6	Times	Decrease ;	21	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	171600	Tablets/hour
Feeder : Status ;	Auto		Speed ;	6	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.00	mm	Pre Thickness ;	2.00	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	3.53	mm	Main Thickness ;	1.03	mm
Filling Depth :	4.70	mm	Current Cam :	Cam B	
Main Air pressure :	0.809	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	24	Min			
Lower Punch Remain Time (S2):	2	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.11	kN		
	Max ;	0.31	kN	Max Punch ;	36
Lower Punch :	Average ;	0.15	kN		
	Max ;	0.19	kN	Max Punch ;	63
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.08	kN	Max Punch ;	63

Tablet Data (N/A)

Total Counter :	31324	Tablets			
A.W.C Counter :	22951	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	22951 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO40mgSTKQ1B00
User ID :	rp98927	Batch NO. :	KQM2507840
Print Interval :	50000 Tablets	Running Time :	00 Hour 11 Min 46 Sec
Total Counter :	31324	Total Running Time :	1862 Hour 21 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	29	%	Manual ;	10	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	31.73	kN	No		
HEP :	25.0 %	30.51	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	24.89	kN	Yes 15	Times	
Ref :		24.41	kN			
LCP :	2.0 %	23.92	kN	Yes 15	Times	
LEP :	25.0 %	18.31	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	17.08	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.02	kN	Min :	0.95	kN	Punch NO.;	63
SD :	2.40	%	Max :	1.11	kN	Punch NO.;	43
Mean Main Pressure :	24.66	kN	Min :	23.11	kN	Punch NO.;	16
SD :	3.50	%	Max :	26.88	kN	Punch NO.;	1
Filling Depth :	Increase ; 5	Times	Decrease ;	1	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	171600	Tablets/hour
Feeder : Status ;	Auto		Speed ;	6	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.00	mm	Pre Thickness ;	2.00	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	3.53	mm	Main Thickness ;	1.03	mm
Filling Depth :	4.34	mm	Current Cam :	Cam B	
Main Air pressure :	0.809	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	24	Min			
Lower Punch Remain Time (S2):	2	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.09	kN		
	Max ;	0.31	kN	Max Punch ;	36
Lower Punch :	Average ;	0.15	kN		
	Max ;	0.19	kN	Max Punch ;	63
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.08	kN	Max Punch ;	63

Tablet Data (N/A)

Total Counter :	31324	Tablets			
A.W.C Counter :	22951	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	22951 (100.0%)	Tablets			