

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO40mgSTKQ1B00
User ID :	sj97904	Batch NO. :	KQM2507840
Print Interval :	50000 Tablets	Running Time :	02 Hour 38 Min 12 Sec
Total Counter :	450262	Total Running Time :	1864 Hour 48 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	29	%	Manual ;	30	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	33.18	kN	No		
HEP :	25.0 %	31.90	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	26.03	kN	Yes 15	Times	
Ref :		25.52	kN			
LCP :	2.0 %	25.01	kN	Yes 15	Times	
LEP :	25.0 %	19.14	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	17.87	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	0.98	kN	Min :	0.92	kN	Punch NO.;	17
SD :	2.60	%	Max :	1.04	kN	Punch NO.;	3
Mean Main Pressure :	25.70	kN	Min :	23.71	kN	Punch NO.;	17
SD :	4.40	%	Max :	28.21	kN	Punch NO.;	46
Filling Depth :	Increase ; 96	Times	Decrease ;	116	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	6	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.00	mm	Pre Thickness ;	2.00	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	3.53	mm	Main Thickness ;	1.03	mm
Filling Depth :	4.85	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.802	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	41	Min			
Lower Punch Remain Time (S2):	19	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.01	kN	Max Punch ;	36
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.16	kN	Max Punch ;	43
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.05	kN	Max Punch ;	63

Tablet Data (N/A)

Total Counter :	450262	Tablets			
A.W.C Counter :	438960	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	438959 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO40mgSTKQ1B00
User ID :	sj97904	Batch NO. :	KQM2507840
Print Interval :	50000 Tablets	Running Time :	02 Hour 38 Min 12 Sec
Total Counter :	450262	Total Running Time :	1864 Hour 48 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	29	%	Manual ;	10	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	31.99	kN	No		
HEP :	25.0 %	30.76	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	25.10	kN	Yes	15	Times
Ref :		24.60	kN			
LCP :	2.0 %	24.11	kN	Yes	15	Times
LEP :	25.0 %	18.45	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	17.22	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	0.96	kN	Min :	0.92	kN	Punch NO.;	15
SD :	2.30	%	Max :	1.02	kN	Punch NO.;	43
Mean Main Pressure :	24.61	kN	Min :	23.07	kN	Punch NO.;	60
SD :	3.50	%	Max :	26.79	kN	Punch NO.;	49
Filling Depth :	Increase ;	8	Times	Decrease ;	9	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	6	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.00	mm	Pre Thickness ;	2.00	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	3.53	mm	Main Thickness ;	1.03	mm
Filling Depth :	4.30	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.802	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	41	Min			
Lower Punch Remain Time (S2):	19	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.01	kN	Max Punch ;	36
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.16	kN	Max Punch ;	43
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.05	kN	Max Punch ;	19

Tablet Data (N/A)

Total Counter :	450262	Tablets			
A.W.C Counter :	438960	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	438959 (100.0%)	Tablets			