

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO40mgSTKQ1B00
User ID :	sj97904	Batch NO. :	KQM2507840
Print Interval :	50000 Tablets	Running Time :	07 Hour 17 Min 41 Sec
Total Counter :	1250636	Total Running Time :	1869 Hour 28 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	36	%	Manual ;	30	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	33.25	kN	No		
HEP :	25.0 %	31.97	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	26.09	kN	Yes 15	Times	
Ref :		25.58	kN			
LCP :	2.0 %	25.07	kN	Yes 15	Times	
LEP :	25.0 %	19.18	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	17.90	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	0.95	kN	Min :	0.91	kN	Punch NO.;	58
SD :	2.30	%	Max :	1.01	kN	Punch NO.;	46
Mean Main Pressure :	25.72	kN	Min :	23.25	kN	Punch NO.;	58
SD :	4.30	%	Max :	28.58	kN	Punch NO.;	46
Filling Depth :	Increase ;	336	Times	Decrease ;	394	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	171600	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.00	mm	Pre Thickness ;	2.00	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	3.53	mm	Main Thickness ;	1.03	mm
Filling Depth :	4.61	mm	Current Cam :	Cam B	
Main Air pressure :	0.800	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	4	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.03	kN	Max Punch ;	36
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.17	kN	Max Punch ;	43
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.04	kN	Max Punch ;	19

Tablet Data (N/A)

Total Counter :	1250636	Tablets			
A.W.C Counter :	1238781	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	261 (0.0%)	Tablets
GOOD :	1238519 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO40mgSTKQ1B00
User ID :	sj97904	Batch NO. :	KQM2507840
Print Interval :	50000 Tablets	Running Time :	07 Hour 17 Min 41 Sec
Total Counter :	1250636	Total Running Time :	1869 Hour 28 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	29	%	Manual ;	10	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	32.63	kN	No		
HEP :	25.0 %	31.38	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	25.60	kN	Yes 15	Times	
Ref :		25.10	kN			
LCP :	2.0 %	24.60	kN	Yes 15	Times	
LEP :	25.0 %	18.83	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	17.57	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	0.96	kN	Min :	0.92	kN	Punch NO.;	18
SD :	2.00	%	Max :	1.01	kN	Punch NO.;	7
Mean Main Pressure :	24.87	kN	Min :	22.95	kN	Punch NO.;	19
SD :	3.90	%	Max :	27.69	kN	Punch NO.;	49
Filling Depth :	Increase ; 35	Times	Decrease ; 51	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	171600	Tablets/hour
Feeder : Status ;	Auto		Speed ;	6	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.00	mm	Pre Thickness ;	2.00	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	3.53	mm	Main Thickness ;	1.03	mm
Filling Depth :	4.34	mm	Current Cam :	Cam B	
Main Air pressure :	0.800	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	4	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.03	kN	Max Punch ;	61
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.17	kN	Max Punch ;	43
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.04	kN	Max Punch ;	19

Tablet Data (N/A)

Total Counter :	1250636	Tablets			
A.W.C Counter :	1238781	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	261 (0.0%)	Tablets
GOOD :	1238519 (100.0%)	Tablets			