

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO40mgSTKQ1B00
User ID :	rp98927	Batch NO. :	KQM2507840
Print Interval :	50000 Tablets	Running Time :	14 Hour 47 Min 39 Sec
Total Counter :	2539148	Total Running Time :	1876 Hour 59 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	36	%	Manual ;	30	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	33.86	kN	No		
HEP :	25.0 %	32.56	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	26.57	kN	Yes 15	Times	
Ref :		26.05	kN			
LCP :	2.0 %	25.53	kN	Yes 15	Times	
LEP :	25.0 %	19.54	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	18.23	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.04	kN	Min :	0.99	kN	Punch NO.;	36
SD :	2.90	%	Max :	1.13	kN	Punch NO.;	27
Mean Main Pressure :	25.94	kN	Min :	23.81	kN	Punch NO.;	60
SD :	4.10	%	Max :	29.39	kN	Punch NO.;	27
Filling Depth :	Increase ; 163	Times	Decrease ;	175	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	171600	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.85	mm	Pre Thickness ;	1.86	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	3.53	mm	Main Thickness ;	1.03	mm
Filling Depth :	5.09	mm	Current Cam :	Cam B	
Main Air pressure :	0.752	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	54	Min			
Lower Punch Remain Time (S2):	12	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.13	kN	Max Punch ;	42
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.16	kN	Max Punch ;	43
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.03	kN	Max Punch ;	6

Tablet Data (N/A)

Total Counter :	2539148	Tablets			
A.W.C Counter :	2526155	Tablets			
HEP :	2 (0.0%)	Tablets	LEP :	574 (0.0%)	Tablets
GOOD :	2525579 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	PANTO40mgSTKQ1B00
User ID :	rp98927	Batch NO. :	KQM2507840
Print Interval :	50000 Tablets	Running Time :	14 Hour 47 Min 39 Sec
Total Counter :	2539148	Total Running Time :	1876 Hour 59 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	29	%	Manual ;	10	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2750000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	34.36	kN	No		
HEP :	25.0 %	33.04	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	26.96	kN	Yes 15	Times	
Ref :		26.43	kN			
LCP :	2.0 %	25.90	kN	Yes 15	Times	
LEP :	25.0 %	19.82	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	18.50	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.03	kN	Min :	0.98	kN	Punch NO.;	26
SD :	2.90	%	Max :	1.11	kN	Punch NO.;	40
Mean Main Pressure :	26.50	kN	Min :	24.94	kN	Punch NO.;	24
SD :	3.00	%	Max :	28.26	kN	Punch NO.;	1
Filling Depth :	Increase ; 48	Times	Decrease ; 49	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	171600	Tablets/hour
Feeder : Status ;	Auto		Speed ;	6	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.85	mm	Pre Thickness ;	1.86	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	3.53	mm	Main Thickness ;	1.03	mm
Filling Depth :	4.56	mm	Current Cam :	Cam B	
Main Air pressure :	0.752	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	54	Min			
Lower Punch Remain Time (S2):	12	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.11	kN	Max Punch ;	45
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.16	kN	Max Punch ;	43
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.03	kN	Max Punch ;	6

Tablet Data (N/A)

Total Counter :	2539148	Tablets			
A.W.C Counter :	2526155	Tablets			
HEP :	2 (0.0%)	Tablets	LEP :	574 (0.0%)	Tablets
GOOD :	2525579 (100.0%)	Tablets			