

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET500MGSTMR7A00
User ID :	ks99394	Batch NO. :	MRM2502150
Print Interval :	50000 Tablets	Running Time :	02 Hour 31 Min 39 Sec
Total Counter :	400142	Total Running Time :	1880 Hour 44 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	89	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.01	kN	No		
HEP :	25.0 %	18.28	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	14.92	kN	Yes 15	Times	
Ref :		14.62	kN			
LCP :	2.0 %	14.33	kN	Yes 15	Times	
LEP :	25.0 %	10.97	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	10.24	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.29	kN	Min :	1.23	kN	Punch NO.;	24
SD :	1.90	%	Max :	1.35	kN	Punch NO.;	43
Mean Main Pressure :	14.67	kN	Min :	14.08	kN	Punch NO.;	2
SD :	1.90	%	Max :	15.23	kN	Punch NO.;	9
Filling Depth :	Increase ; 36	Times	Decrease ; 38	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	2.49	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.51	mm
Main Upper Punch Position ;	2.49	mm			
Main Lower Punch Position ;	5.60	mm	Main Thickness ;	3.11	mm
Filling Depth :	7.37	mm	Current Cam :	Cam C	
Main Air pressure :	0.802	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	70	Min			
Lower Punch Remain Time (S2):	8	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.21	kN		
	Max ;	0.29	kN	Max Punch ;	6
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.35	kN	Max Punch ;	20
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	400142	Tablets			
A.W.C Counter :	389369	Tablets			
HEP :	0 (0%)	Tablets	LEP :	120 (0.0%)	Tablets
GOOD :	389249 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET500MGSTMR7A00
User ID :	ks99394	Batch NO. :	MRM2502150
Print Interval :	50000 Tablets	Running Time :	02 Hour 31 Min 39 Sec
Total Counter :	400142	Total Running Time :	1880 Hour 44 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	89	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.94	kN	No		
HEP :	25.0 %	18.21	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	14.86	kN	Yes 15	Times	
Ref :		14.57	kN			
LCP :	2.0 %	14.27	kN	Yes 15	Times	
LEP :	25.0 %	10.92	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	10.20	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.32	kN	Min :	1.18	kN	Punch NO.;	24
SD :	2.60	%	Max :	1.38	kN	Punch NO.;	20
Mean Main Pressure :	14.41	kN	Min :	13.78	kN	Punch NO.;	44
SD :	2.80	%	Max :	15.18	kN	Punch NO.;	27
Filling Depth :	Increase ; 23	Times	Decrease ; 22	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	2.49	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.51	mm
Main Upper Punch Position ;	2.49	mm			
Main Lower Punch Position ;	5.56	mm	Main Thickness ;	3.07	mm
Filling Depth :	6.68	mm	Current Cam :	Cam C	
Main Air pressure :	0.802	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	70	Min			
Lower Punch Remain Time (S2):	8	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.21	kN		
	Max ;	0.29	kN	Max Punch ;	6
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.35	kN	Max Punch ;	20
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	400142	Tablets			
A.W.C Counter :	389369	Tablets			
HEP :	0 (0%)	Tablets	LEP :	120 (0.0%)	Tablets
GOOD :	389249 (100.0%)	Tablets			