

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET500MGSTMR7A00
User ID :	rp98927	Batch NO. :	MRM2502150
Print Interval :	50000 Tablets	Running Time :	18 Hour 09 Min 09 Sec
Total Counter :	2886580	Total Running Time :	1896 Hour 22 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	89	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	20.27	kN	No		
HEP :	25.0 %	19.49	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	15.90	kN	Yes 15	Times	
Ref :		15.59	kN			
LCP :	2.0 %	15.28	kN	Yes 15	Times	
LEP :	25.0 %	11.69	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	10.91	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.39	kN	Min :	1.33	kN	Punch NO.;	8
SD :	2.10	%	Max :	1.46	kN	Punch NO.;	16
Mean Main Pressure :	15.68	kN	Min :	15.03	kN	Punch NO.;	30
SD :	2.10	%	Max :	16.41	kN	Punch NO.;	1
Filling Depth :	Increase ; 37	Times	Decrease ; 50	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	2.49	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.51	mm
Main Upper Punch Position ;	2.49	mm			
Main Lower Punch Position ;	5.59	mm	Main Thickness ;	3.10	mm
Filling Depth :	7.45	mm	Current Cam :	Cam C	
Main Air pressure :	0.725	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	76	Min			
Lower Punch Remain Time (S2):	10	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.06	kN		
	Max ;	0.11	kN	Max Punch ;	35
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.20	kN	Max Punch ;	27
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2886580	Tablets			
A.W.C Counter :	2872560	Tablets			
HEP :	0 (0%)	Tablets	LEP :	225 (0.0%)	Tablets
GOOD :	2872335 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET500MGSTMR7A00
User ID :	rp98927	Batch NO. :	MRM2502150
Print Interval :	50000 Tablets	Running Time :	18 Hour 09 Min 09 Sec
Total Counter :	2886580	Total Running Time :	1896 Hour 22 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	89	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.33	kN	No		
HEP :	25.0 %	18.59	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	15.17	kN	Yes 15	Times	
Ref :		14.87	kN			
LCP :	2.0 %	14.57	kN	Yes 15	Times	
LEP :	25.0 %	11.15	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	10.41	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	1.62	kN	Min :	1.46	kN	Punch NO.;	48
		3.80	%	Max :	1.88	kN	Punch NO.;	47
Mean Main Pressure :		14.86	kN	Min :	13.85	kN	Punch NO.;	8
	SD :	3.00	%	Max :	16.33	kN	Punch NO.;	7
Filling Depth :	Increase ;	46	Times	Decrease ;	45	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	2.49	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	3.31	mm
Main Upper Punch Position ;	2.49	mm			
Main Lower Punch Position ;	5.60	mm	Main Thickness ;	3.11	mm
Filling Depth :	7.42	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.725	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	76	Min			
Lower Punch Remain Time (S2):	10	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.06	kN		
	Max ;	0.11	kN	Max Punch ;	35
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.19	kN	Max Punch ;	27
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2886580	Tablets			
A.W.C Counter :	2872560	Tablets			
HEP :	0 (0%)	Tablets	LEP :	225 (0.0%)	Tablets
GOOD :	2872335 (100.0%)	Tablets			