

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET500MGSTMR7A00
User ID :	sj97904	Batch NO. :	MRM2502150
Print Interval :	50000 Tablets	Running Time :	23 Hour 10 Min 58 Sec
Total Counter :	3687040	Total Running Time :	1901 Hour 24 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	89	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	20.53	kN	No		
HEP :	25.0 %	19.74	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	16.11	kN	Yes 15	Times	
Ref :		15.79	kN			
LCP :	2.0 %	15.47	kN	Yes 15	Times	
LEP :	25.0 %	11.84	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	11.05	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.37	kN	Min :	1.33	kN	Punch NO.;	28
SD :	2.00	%	Max :	1.44	kN	Punch NO.;	43
Mean Main Pressure :	15.79	kN	Min :	15.12	kN	Punch NO.;	41
SD :	2.10	%	Max :	16.62	kN	Punch NO.;	37
Filling Depth :	Increase ; 60	Times	Decrease ;	75	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	2.49	mm			
Pre Lower Punch Position ;	6.00	mm	Pre Thickness ;	3.51	mm
Main Upper Punch Position ;	2.49	mm			
Main Lower Punch Position ;	5.59	mm	Main Thickness ;	3.10	mm
Filling Depth :	7.46	mm	Current Cam :	Cam C	
Main Air pressure :	0.759	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	15	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.07	kN		
	Max ;	0.13	kN	Max Punch ;	34
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.19	kN	Max Punch ;	52
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	3687040	Tablets			
A.W.C Counter :	3672897	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	225 (0.0%)	Tablets
GOOD :	3672671 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET500MGSTMR7A00
User ID :	sj97904	Batch NO. :	MRM2502150
Print Interval :	50000 Tablets	Running Time :	23 Hour 10 Min 58 Sec
Total Counter :	3687040	Total Running Time :	1901 Hour 24 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	89	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.33	kN	No		
HEP :	25.0 %	18.59	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	15.17	kN	Yes 15	Times	
Ref :		14.87	kN			
LCP :	2.0 %	14.57	kN	Yes 15	Times	
LEP :	25.0 %	11.15	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	10.41	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	1.65	kN	Min :	1.55	kN	Punch NO.;	6
		3.40	%	Max :	1.80	kN	Punch NO.;	40
Mean Main Pressure :		15.05	kN	Min :	14.26	kN	Punch NO.;	41
	SD :	2.80	%	Max :	16.00	kN	Punch NO.;	53
Filling Depth :	Increase ;	92	Times	Decrease ;	92	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	2.49	mm			
Pre Lower Punch Position ;	5.80	mm	Pre Thickness ;	3.31	mm
Main Upper Punch Position ;	2.49	mm			
Main Lower Punch Position ;	5.60	mm	Main Thickness ;	3.11	mm
Filling Depth :	7.39	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.759	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	15	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.07	kN		
	Max ;	0.13	kN	Max Punch ;	34
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.19	kN	Max Punch ;	52
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	3687040	Tablets			
A.W.C Counter :	3672897	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	225 (0.0%)	Tablets
GOOD :	3672671 (100.0%)	Tablets			