

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	pb97604	Batch NO. :	SHM2502350
Print Interval :	50000 Tablets	Running Time :	13 Hour 37 Min 35 Sec
Total Counter :	3452488	Total Running Time :	1948 Hour 21 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	42	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.50	kN	No		
HEP :	25.0 %	15.87	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	12.89	kN	Yes 15	Times	
Ref :		12.70	kN			
LCP :	1.5 %	12.51	kN	Yes 15	Times	
LEP :	25.0 %	9.52	kN	No 35	Rotations 35	Tablets
LSP :	30.0 %	8.89	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.94	kN	Min :	1.82	kN	Punch NO.;	65
SD :	2.10	%	Max :	2.04	kN	Punch NO.;	63
Mean Main Pressure :	12.61	kN	Min :	11.57	kN	Punch NO.;	58
SD :	3.90	%	Max :	13.87	kN	Punch NO.;	63
Filling Depth :	Increase ;	143	Times	Decrease ;	182	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	2.60	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.11	mm	Main Thickness ;	2.11	mm
Filling Depth :	5.85	mm	Current Cam :	Cam B	
Main Air pressure :	0.796	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	40	Min			
Lower Punch Remain Time (S2):	19	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.10	kN		
	Max ;	0.20	kN	Max Punch ;	63
Lower Punch :	Average ;	0.06	kN		
	Max ;	0.09	kN	Max Punch ;	70
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	3452488	Tablets			
A.W.C Counter :	3432759	Tablets			
HEP :	178 (0.0%)	Tablets	LEP :	8576 (0.2%)	Tablets
GOOD :	3424005 (99.7%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	pb97604	Batch NO. :	SHM2502350
Print Interval :	50000 Tablets	Running Time :	13 Hour 37 Min 35 Sec
Total Counter :	3452488	Total Running Time :	1948 Hour 21 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	38	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	15.77	kN	No		
HEP :	25.0 %	15.17	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	12.32	kN	Yes 15	Times	
Ref :		12.13	kN			
LCP :	1.5 %	11.95	kN	Yes 15	Times	
LEP :	25.0 %	9.10	kN	Yes 35	Rotations 35	Tablets
LSP :	30.0 %	8.49	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.94	kN	Min :	1.84	kN	Punch NO.;	8
SD :	2.10	%	Max :	2.03	kN	Punch NO.;	63
Mean Main Pressure :	12.20	kN	Min :	11.22	kN	Punch NO.;	8
SD :	3.10	%	Max :	12.91	kN	Punch NO.;	25
Filling Depth :	Increase ;	123	Times	Decrease ;	179	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	11	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.50	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.22	mm	Main Thickness ;	2.22	mm
Filling Depth :	5.51	mm	Current Cam :	Cam B	
Main Air pressure :	0.796	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	40	Min			
Lower Punch Remain Time (S2):	19	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.10	kN		
	Max ;	0.20	kN	Max Punch ;	63
Lower Punch :	Average ;	0.06	kN		
	Max ;	0.09	kN	Max Punch ;	70
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	3452488	Tablets			
A.W.C Counter :	3432759	Tablets			
HEP :	178 (0.0%)	Tablets	LEP :	8576 (0.2%)	Tablets
GOOD :	3424005 (99.7%)	Tablets			