

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	pb97604	Batch NO. :	SHM2502350
Print Interval :	50000 Tablets	Running Time :	14 Hour 47 Min 09 Sec
Total Counter :	3752652	Total Running Time :	1949 Hour 31 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	42	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.43	kN	No		
HEP :	25.0 %	16.76	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	13.61	kN	Yes 15	Times	
Ref :		13.41	kN			
LCP :	1.5 %	13.20	kN	Yes 15	Times	
LEP :	25.0 %	10.05	kN	No 35	Rotations 35	Tablets
LSP :	30.0 %	9.38	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.98	kN	Min :	1.80	kN	Punch NO.;	65
SD :	2.60	%	Max :	2.08	kN	Punch NO.;	23
Mean Main Pressure :	13.40	kN	Min :	11.47	kN	Punch NO.;	64
SD :	4.10	%	Max :	14.40	kN	Punch NO.;	71
Filling Depth :	Increase ; 146	Times	Decrease ;	210	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	2.60	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.11	mm	Main Thickness ;	2.11	mm
Filling Depth :	6.30	mm	Current Cam :	Cam B	
Main Air pressure :	0.814	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	51	Min			
Lower Punch Remain Time (S2):	10	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.10	kN		
	Max ;	0.19	kN	Max Punch ;	69
Lower Punch :	Average ;	0.06	kN		
	Max ;	0.10	kN	Max Punch ;	70
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	3752652	Tablets			
A.W.C Counter :	3732905	Tablets			
HEP :	178 (0.0%)	Tablets	LEP :	8576 (0.2%)	Tablets
GOOD :	3724151 (99.8%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	pb97604	Batch NO. :	SHM2502350
Print Interval :	50000 Tablets	Running Time :	14 Hour 47 Min 09 Sec
Total Counter :	3752652	Total Running Time :	1949 Hour 31 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	38	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.66	kN	No		
HEP :	25.0 %	16.02	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	13.00	kN	Yes 15	Times	
Ref :		12.81	kN			
LCP :	1.5 %	12.62	kN	Yes 15	Times	
LEP :	25.0 %	9.61	kN	Yes 35	Rotations 35	Tablets
LSP :	30.0 %	8.97	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.99	kN	Min :	1.86	kN	Punch NO.;	64
SD :	2.90	%	Max :	2.19	kN	Punch NO.;	5
Mean Main Pressure :	12.83	kN	Min :	11.77	kN	Punch NO.;	64
SD :	3.80	%	Max :	14.36	kN	Punch NO.;	5
Filling Depth :	Increase ;	131	Times	Decrease ;	196	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	11	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.50	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.22	mm	Main Thickness ;	2.22	mm
Filling Depth :	5.56	mm	Current Cam :	Cam B	
Main Air pressure :	0.814	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	51	Min			
Lower Punch Remain Time (S2):	10	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.10	kN		
	Max ;	0.19	kN	Max Punch ;	69
Lower Punch :	Average ;	0.06	kN		
	Max ;	0.10	kN	Max Punch ;	70
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	3752652	Tablets			
A.W.C Counter :	3732905	Tablets			
HEP :	178 (0.0%)	Tablets	LEP :	8576 (0.2%)	Tablets
GOOD :	3724151 (99.8%)	Tablets			