

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	pb97604	Batch NO. :	SHM2502350
Print Interval :	50000 Tablets	Running Time :	16 Hour 31 Min 31 Sec
Total Counter :	4203130	Total Running Time :	1951 Hour 15 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	42	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.57	kN	No		
HEP :	25.0 %	16.90	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	13.72	kN	Yes 15	Times	
Ref :		13.52	kN			
LCP :	1.5 %	13.32	kN	Yes 15	Times	
LEP :	25.0 %	10.14	kN	No 35	Rotations 35	Tablets
LSP :	30.0 %	9.46	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.97	kN	Min :	1.78	kN	Punch NO.;	65
SD :	2.40	%	Max :	2.06	kN	Punch NO.;	6
Mean Main Pressure :	13.52	kN	Min :	11.65	kN	Punch NO.;	65
SD :	4.20	%	Max :	14.68	kN	Punch NO.;	73
Filling Depth :	Increase ;	169	Times	Decrease ;	236	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	2.60	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.11	mm	Main Thickness ;	2.11	mm
Filling Depth :	6.35	mm	Current Cam :	Cam B	
Main Air pressure :	0.802	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	26	Min			
Lower Punch Remain Time (S2):	5	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.11	kN		
	Max ;	0.19	kN	Max Punch ;	63
Lower Punch :	Average ;	0.06	kN		
	Max ;	0.10	kN	Max Punch ;	70
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	4203130	Tablets			
A.W.C Counter :	4183432	Tablets			
HEP :	178 (0.0%)	Tablets	LEP :	8576 (0.2%)	Tablets
GOOD :	4174678 (99.8%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	pb97604	Batch NO. :	SHM2502350
Print Interval :	50000 Tablets	Running Time :	16 Hour 31 Min 31 Sec
Total Counter :	4203130	Total Running Time :	1951 Hour 15 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	38	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.03	kN	No		
HEP :	25.0 %	16.38	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	13.30	kN	Yes 15	Times	
Ref :		13.10	kN			
LCP :	1.5 %	12.91	kN	Yes 15	Times	
LEP :	25.0 %	9.83	kN	Yes 35	Rotations 35	Tablets
LSP :	30.0 %	9.17	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.02	kN	Min :	1.80	kN	Punch NO.;	65
SD :	3.60	%	Max :	2.18	kN	Punch NO.;	5
Mean Main Pressure :	13.28	kN	Min :	11.45	kN	Punch NO.;	61
SD :	5.20	%	Max :	14.83	kN	Punch NO.;	52
Filling Depth :	Increase ;	179	Times	Decrease ;	243	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	11	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.50	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.22	mm	Main Thickness ;	2.22	mm
Filling Depth :	5.66	mm	Current Cam :	Cam B	
Main Air pressure :	0.802	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	26	Min			
Lower Punch Remain Time (S2):	5	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.11	kN		
	Max ;	0.21	kN	Max Punch ;	52
Lower Punch :	Average ;	0.06	kN		
	Max ;	0.10	kN	Max Punch ;	70
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	4203130	Tablets			
A.W.C Counter :	4183432	Tablets			
HEP :	178 (0.0%)	Tablets	LEP :	8576 (0.2%)	Tablets
GOOD :	4174678 (99.8%)	Tablets			