

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	sj97904	Batch NO. :	SHM2502450
Print Interval :	50000 Tablets	Running Time :	02 Hour 07 Min 46 Sec
Total Counter :	550510	Total Running Time :	1959 Hour 46 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	44	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.43	kN	No		
HEP :	25.0 %	15.79	kN	Yes	10	Rotations 20 Tablets
HCP :	1.5 %	12.83	kN	Yes	15	Times
Ref :		12.64	kN			
LCP :	1.5 %	12.45	kN	Yes	15	Times
LEP :	25.0 %	9.48	kN	No	35	Rotations 35 Tablets
LSP :	30.0 %	8.85	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.95	kN	Min :	1.85	kN	Punch NO.;	19
SD :	1.90	%	Max :	2.04	kN	Punch NO.;	30
Mean Main Pressure :	12.49	kN	Min :	10.99	kN	Punch NO.;	19
SD :	4.00	%	Max :	13.58	kN	Punch NO.;	25
Filling Depth :	Increase ;	279	Times	Decrease ;	360	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	2.60	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.13	mm	Main Thickness ;	2.13	mm
Filling Depth :	5.94	mm	Current Cam :	Cam B	
Main Air pressure :	0.804	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	1	Min			
Lower Punch Remain Time (S2):	20	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.09	kN		
	Max ;	0.20	kN	Max Punch ;	63
Lower Punch :	Average ;	0.06	kN		
	Max ;	0.09	kN	Max Punch ;	58
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	550510	Tablets			
A.W.C Counter :	545449	Tablets			
HEP :	0 (0%)	Tablets	LEP :	198 (0.0%)	Tablets
GOOD :	545251 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	sj97904	Batch NO. :	SHM2502450
Print Interval :	50000 Tablets	Running Time :	02 Hour 07 Min 46 Sec
Total Counter :	550510	Total Running Time :	1959 Hour 46 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	38	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.23	kN	No		
HEP :	25.0 %	15.60	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	12.67	kN	Yes 15	Times	
Ref :		12.48	kN			
LCP :	1.5 %	12.30	kN	Yes 15	Times	
LEP :	25.0 %	9.36	kN	Yes 35	Rotations 35	Tablets
LSP :	30.0 %	8.74	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.00	kN	Min :	1.88	kN	Punch NO.;	16
SD :	2.60	%	Max :	2.13	kN	Punch NO.;	8
Mean Main Pressure :	12.55	kN	Min :	11.63	kN	Punch NO.;	19
SD :	3.90	%	Max :	13.79	kN	Punch NO.;	1
Filling Depth :	Increase ;	280	Times	Decrease ;	356	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	11	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.50	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.23	mm	Main Thickness ;	2.23	mm
Filling Depth :	5.58	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.804	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	1	Min			
Lower Punch Remain Time (S2):	20	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.09	kN		
	Max ;	0.20	kN	Max Punch ;	63
Lower Punch :	Average ;	0.06	kN		
	Max ;	0.09	kN	Max Punch ;	58
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	550510	Tablets			
A.W.C Counter :	545449	Tablets			
HEP :	0 (0%)	Tablets	LEP :	198 (0.0%)	Tablets
GOOD :	545251 (100.0%)	Tablets			