

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	sj97904	Batch NO. :	SHM2502450
Print Interval :	50000 Tablets	Running Time :	02 Hour 30 Min 57 Sec
Total Counter :	650554	Total Running Time :	1960 Hour 9 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	44	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.43	kN	No		
HEP :	25.0 %	15.79	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	12.83	kN	Yes 15	Times	
Ref :		12.64	kN			
LCP :	1.5 %	12.45	kN	Yes 15	Times	
LEP :	25.0 %	9.48	kN	No 35	Rotations 35	Tablets
LSP :	30.0 %	8.85	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.96	kN	Min :	1.88	kN	Punch NO.;	19
SD :	2.00	%	Max :	2.06	kN	Punch NO.;	23
Mean Main Pressure :	12.57	kN	Min :	11.52	kN	Punch NO.;	19
SD :	3.50	%	Max :	13.53	kN	Punch NO.;	40
Filling Depth :	Increase ;	280	Times	Decrease ;	360	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	2.60	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.13	mm	Main Thickness ;	2.13	mm
Filling Depth :	5.97	mm	Current Cam :	Cam B	
Main Air pressure :	0.797	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	58	Min			
Lower Punch Remain Time (S2):	17	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.08	kN		
	Max ;	0.19	kN	Max Punch ;	63
Lower Punch :	Average ;	0.06	kN		
	Max ;	0.09	kN	Max Punch ;	70
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	650554	Tablets			
A.W.C Counter :	645472	Tablets			
HEP :	0 (0%)	Tablets	LEP :	198 (0.0%)	Tablets
GOOD :	645274 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	sj97904	Batch NO. :	SHM2502450
Print Interval :	50000 Tablets	Running Time :	02 Hour 30 Min 57 Sec
Total Counter :	650554	Total Running Time :	1960 Hour 9 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	38	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.23	kN	No		
HEP :	25.0 %	15.60	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	12.67	kN	Yes 15	Times	
Ref :		12.48	kN			
LCP :	1.5 %	12.30	kN	Yes 15	Times	
LEP :	25.0 %	9.36	kN	Yes 35	Rotations 35	Tablets
LSP :	30.0 %	8.74	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.99	kN	Min :	1.85	kN	Punch NO.;	26
SD :	2.90	%	Max :	2.15	kN	Punch NO.;	72
Mean Main Pressure :	12.46	kN	Min :	11.30	kN	Punch NO.;	14
SD :	4.40	%	Max :	13.79	kN	Punch NO.;	77
Filling Depth :	Increase ;	291	Times	Decrease ;	367	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	11	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.50	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.23	mm	Main Thickness ;	2.23	mm
Filling Depth :	5.58	mm	Current Cam :	Cam B	
Main Air pressure :	0.797	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	58	Min			
Lower Punch Remain Time (S2):	17	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.09	kN		
	Max ;	0.18	kN	Max Punch ;	63
Lower Punch :	Average ;	0.06	kN		
	Max ;	0.09	kN	Max Punch ;	70
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	650554	Tablets			
A.W.C Counter :	645472	Tablets			
HEP :	0 (0%)	Tablets	LEP :	198 (0.0%)	Tablets
GOOD :	645274 (100.0%)	Tablets			