

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	pb97604	Batch NO. :	SHM2502450
Print Interval :	50000 Tablets	Running Time :	07 Hour 09 Min 13 Sec
Total Counter :	1851680	Total Running Time :	1964 Hour 48 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	46	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.78	kN	No		
HEP :	25.0 %	16.14	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	13.10	kN	Yes 15	Times	
Ref :		12.91	kN			
LCP :	1.5 %	12.71	kN	Yes 15	Times	
LEP :	25.0 %	9.68	kN	No 35	Rotations 35	Tablets
LSP :	30.0 %	9.04	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.90	kN	Min :	1.76	kN	Punch NO.;	65
SD :	2.20	%	Max :	2.01	kN	Punch NO.;	38
Mean Main Pressure :	12.78	kN	Min :	11.48	kN	Punch NO.;	59
SD :	3.80	%	Max :	13.80	kN	Punch NO.;	16
Filling Depth :	Increase ; 363	Times	Decrease ; 432	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	13	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	2.60	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.13	mm	Main Thickness ;	2.13	mm
Filling Depth :	6.31	mm	Current Cam :	Cam B	
Main Air pressure :	0.792	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	20	Min			
Lower Punch Remain Time (S2):	19	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.11	kN		
	Max ;	0.20	kN	Max Punch ;	7
Lower Punch :	Average ;	0.06	kN		
	Max ;	0.09	kN	Max Punch ;	70
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1851680	Tablets			
A.W.C Counter :	1846595	Tablets			
HEP :	0 (0%)	Tablets	LEP :	198 (0.0%)	Tablets
GOOD :	1846397 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	pb97604	Batch NO. :	SHM2502450
Print Interval :	50000 Tablets	Running Time :	07 Hour 09 Min 13 Sec
Total Counter :	1851680	Total Running Time :	1964 Hour 48 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	42	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.75	kN	No		
HEP :	25.0 %	16.10	kN	Yes	10	Rotations 20 Tablets
HCP :	1.5 %	13.07	kN	Yes	15	Times
Ref :		12.88	kN			
LCP :	1.5 %	12.69	kN	Yes	15	Times
LEP :	25.0 %	9.66	kN	Yes	35	Rotations 35 Tablets
LSP :	30.0 %	9.02	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.95	kN	Min :	1.80	kN	Punch NO.;	62
SD :	2.80	%	Max :	2.15	kN	Punch NO.;	8
Mean Main Pressure :	12.96	kN	Min :	11.47	kN	Punch NO.;	26
SD :	4.70	%	Max :	15.26	kN	Punch NO.;	8
Filling Depth :	Increase ;	338	Times	Decrease ;	417	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.50	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.23	mm	Main Thickness ;	2.23	mm
Filling Depth :	5.60	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.792	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	20	Min			
Lower Punch Remain Time (S2):	19	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.11	kN		
	Max ;	0.20	kN	Max Punch ;	7
Lower Punch :	Average ;	0.06	kN		
	Max ;	0.09	kN	Max Punch ;	70
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1851680	Tablets			
A.W.C Counter :	1846595	Tablets			
HEP :	0 (0%)	Tablets	LEP :	198 (0.0%)	Tablets
GOOD :	1846397 (100.0%)	Tablets			