

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	rp98927	Batch NO. :	SHM2502450
Print Interval :	50000 Tablets	Running Time :	11 Hour 47 Min 24 Sec
Total Counter :	3052408	Total Running Time :	1969 Hour 26 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	46	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.41	kN	No		
HEP :	25.0 %	16.74	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	13.59	kN	Yes 15	Times	
Ref :		13.39	kN			
LCP :	1.5 %	13.19	kN	Yes 15	Times	
LEP :	25.0 %	10.04	kN	No 35	Rotations 35	Tablets
LSP :	30.0 %	9.38	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.92	kN	Min :	1.81	kN	Punch NO.;	59
SD :	2.10	%	Max :	2.01	kN	Punch NO.;	22
Mean Main Pressure :	13.29	kN	Min :	11.77	kN	Punch NO.;	59
SD :	4.40	%	Max :	14.28	kN	Punch NO.;	8
Filling Depth :	Increase ;	392	Times	Decrease ;	491	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	13	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	2.60	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.13	mm	Main Thickness ;	2.13	mm
Filling Depth :	5.97	mm	Current Cam :	Cam B	
Main Air pressure :	0.791	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	62	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.11	kN		
	Max ;	0.20	kN	Max Punch ;	6
Lower Punch :	Average ;	0.06	kN		
	Max ;	0.09	kN	Max Punch ;	7
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	3052408	Tablets			
A.W.C Counter :	3047223	Tablets			
HEP :	0 (0%)	Tablets	LEP :	198 (0.0%)	Tablets
GOOD :	3047025 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	rp98927	Batch NO. :	SHM2502450
Print Interval :	50000 Tablets	Running Time :	11 Hour 47 Min 24 Sec
Total Counter :	3052408	Total Running Time :	1969 Hour 26 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	42	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.09	kN	No		
HEP :	25.0 %	16.43	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	13.34	kN	Yes 15	Times	
Ref :		13.14	kN			
LCP :	1.5 %	12.95	kN	Yes 15	Times	
LEP :	25.0 %	9.86	kN	Yes 35	Rotations 35	Tablets
LSP :	30.0 %	9.20	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.96	kN	Min :	1.87	kN	Punch NO.;	28
SD :	2.00	%	Max :	2.08	kN	Punch NO.;	40
Mean Main Pressure :	13.19	kN	Min :	12.30	kN	Punch NO.;	47
SD :	3.60	%	Max :	14.40	kN	Punch NO.;	8
Filling Depth :	Increase ;	375	Times	Decrease ;	455	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.50	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.23	mm	Main Thickness ;	2.23	mm
Filling Depth :	5.70	mm	Current Cam :	Cam B	
Main Air pressure :	0.791	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	62	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.11	kN		
	Max ;	0.20	kN	Max Punch ;	6
Lower Punch :	Average ;	0.06	kN		
	Max ;	0.09	kN	Max Punch ;	70
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	3052408	Tablets			
A.W.C Counter :	3047223	Tablets			
HEP :	0 (0%)	Tablets	LEP :	198 (0.0%)	Tablets
GOOD :	3047025 (100.0%)	Tablets			