

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	rp98927	Batch NO. :	SHM2502450
Print Interval :	50000 Tablets	Running Time :	14 Hour 52 Min 53 Sec
Total Counter :	3853030	Total Running Time :	1972 Hour 32 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	46	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.41	kN	No		
HEP :	25.0 %	16.74	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	13.59	kN	Yes 15	Times	
Ref :		13.39	kN			
LCP :	1.5 %	13.19	kN	Yes 15	Times	
LEP :	25.0 %	10.04	kN	No 35	Rotations 35	Tablets
LSP :	30.0 %	9.38	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.91	kN	Min :	1.69	kN	Punch NO.;	6
SD :	2.40	%	Max :	2.00	kN	Punch NO.;	50
Mean Main Pressure :	13.36	kN	Min :	10.33	kN	Punch NO.;	6
SD :	4.50	%	Max :	14.42	kN	Punch NO.;	65
Filling Depth :	Increase ;	394	Times	Decrease ;	492	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	13	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	2.60	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.13	mm	Main Thickness ;	2.13	mm
Filling Depth :	6.00	mm	Current Cam :	Cam B	
Main Air pressure :	0.779	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	37	Min			
Lower Punch Remain Time (S2):	16	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.13	kN		
	Max ;	0.25	kN	Max Punch ;	65
Lower Punch :	Average ;	0.06	kN		
	Max ;	0.10	kN	Max Punch ;	6
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	3853030	Tablets			
A.W.C Counter :	3847792	Tablets			
HEP :	0 (0%)	Tablets	LEP :	204 (0.0%)	Tablets
GOOD :	3847588 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	rp98927	Batch NO. :	SHM2502450
Print Interval :	50000 Tablets	Running Time :	14 Hour 52 Min 53 Sec
Total Counter :	3853030	Total Running Time :	1972 Hour 32 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	42	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.09	kN	No		
HEP :	25.0 %	16.43	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	13.34	kN	Yes 15	Times	
Ref :		13.14	kN			
LCP :	1.5 %	12.95	kN	Yes 15	Times	
LEP :	25.0 %	9.86	kN	Yes 35	Rotations 35	Tablets
LSP :	30.0 %	9.20	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.91	kN	Min :	1.79	kN	Punch NO.;	4
SD :	2.10	%	Max :	1.99	kN	Punch NO.;	42
Mean Main Pressure :	12.92	kN	Min :	11.75	kN	Punch NO.;	4
SD :	3.80	%	Max :	14.11	kN	Punch NO.;	52
Filling Depth :	Increase ;	389	Times	Decrease ;	470	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.50	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.23	mm	Main Thickness ;	2.23	mm
Filling Depth :	5.67	mm	Current Cam :	Cam B	
Main Air pressure :	0.779	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	37	Min			
Lower Punch Remain Time (S2):	16	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.12	kN		
	Max ;	0.23	kN	Max Punch ;	65
Lower Punch :	Average ;	0.06	kN		
	Max ;	0.10	kN	Max Punch ;	6
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	3853030	Tablets			
A.W.C Counter :	3847869	Tablets			
HEP :	0 (0%)	Tablets	LEP :	204 (0.0%)	Tablets
GOOD :	3847665 (100.0%)	Tablets			