

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	rp98927	Batch NO. :	SHM2502550
Print Interval :	50000 Tablets	Running Time :	05 Hour 53 Min 49 Sec
Total Counter :	1527006	Total Running Time :	1986 Hour 32 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	46	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.33	kN	No		
HEP :	25.0 %	15.70	kN	Yes	10	Rotations 20 Tablets
HCP :	1.5 %	12.75	kN	Yes	15	Times
Ref :		12.56	kN			
LCP :	1.5 %	12.37	kN	Yes	15	Times
LEP :	25.0 %	9.42	kN	No	35	Rotations 35 Tablets
LSP :	30.0 %	8.79	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.83	kN	Min :	1.71	kN	Punch NO.;	60
SD :	2.30	%	Max :	1.92	kN	Punch NO.;	38
Mean Main Pressure :	12.50	kN	Min :	10.81	kN	Punch NO.;	60
SD :	4.40	%	Max :	13.84	kN	Punch NO.;	73
Filling Depth :	Increase ;	8	Times	Decrease ;	11	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	13	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.59	mm	Pre Thickness ;	2.60	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.13	mm	Main Thickness ;	2.13	mm
Filling Depth :	5.91	mm	Current Cam :	Cam B	
Main Air pressure :	0.777	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	2	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.13	kN		
	Max ;	0.25	kN	Max Punch ;	65
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.08	kN	Max Punch ;	70
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1527006	Tablets			
A.W.C Counter :	1522062	Tablets			
HEP :	7 (0.0%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	1522054 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	rp98927	Batch NO. :	SHM2502550
Print Interval :	50000 Tablets	Running Time :	05 Hour 53 Min 49 Sec
Total Counter :	1527006	Total Running Time :	1986 Hour 32 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	42	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.00	kN	No		
HEP :	25.0 %	15.38	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	12.49	kN	Yes 15	Times	
Ref :		12.31	kN			
LCP :	1.5 %	12.12	kN	Yes 15	Times	
LEP :	25.0 %	9.23	kN	Yes 35	Rotations 35	Tablets
LSP :	30.0 %	8.61	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.86	kN	Min :	1.74	kN	Punch NO.;	19
SD :	2.40	%	Max :	1.98	kN	Punch NO.;	5
Mean Main Pressure :	12.36	kN	Min :	11.26	kN	Punch NO.;	19
SD :	3.60	%	Max :	13.35	kN	Punch NO.;	73
Filling Depth :	Increase ;	5	Times	Decrease ;	10	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.49	mm	Pre Thickness ;	2.49	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.22	mm	Main Thickness ;	2.23	mm
Filling Depth :	5.76	mm	Current Cam :	Cam B	
Main Air pressure :	0.777	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	2	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.12	kN		
	Max ;	0.24	kN	Max Punch ;	70
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.08	kN	Max Punch ;	70
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	1527006	Tablets			
A.W.C Counter :	1522062	Tablets			
HEP :	7 (0.0%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	1522054 (100.0%)	Tablets			