

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	ka98463	Batch NO. :	SHM2502750
Print Interval :	50000 Tablets	Running Time :	01 Hour 57 Min 40 Sec
Total Counter :	500360	Total Running Time :	2028 Hour 39 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	42	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	15.01	kN	No		
HEP :	25.0 %	14.44	kN	Yes	10	Rotations 20 Tablets
HCP :	1.5 %	11.72	kN	Yes	15	Times
Ref :		11.55	kN			
LCP :	1.5 %	11.38	kN	Yes	15	Times
LEP :	25.0 %	8.66	kN	No	35	Rotations 35 Tablets
LSP :	30.0 %	8.08	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	1.36	kN	Min :	1.32	kN	Punch NO.;	41
		1.00	%	Max :	1.39	kN	Punch NO.;	23
Mean Main Pressure :		11.60	kN	Min :	10.21	kN	Punch NO.;	46
	SD :	3.50	%	Max :	12.65	kN	Punch NO.;	73
Filling Depth :	Increase ;	23	Times	Decrease ;	37	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.20	mm	Main Thickness ;	2.21	mm
Filling Depth :	5.87	mm	Current Cam :	Cam B	
Main Air pressure :	0.757	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	54	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.15	kN		
	Max ;	0.18	kN	Max Punch ;	42
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.12	kN	Max Punch ;	55
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.06	kN	Max Punch ;	37

Tablet Data (N/A)

Total Counter :	500360	Tablets			
A.W.C Counter :	484538	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	223 (0.0%)	Tablets
GOOD :	484314 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	ka98463	Batch NO. :	SHM2502750
Print Interval :	50000 Tablets	Running Time :	01 Hour 57 Min 40 Sec
Total Counter :	500360	Total Running Time :	2028 Hour 39 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	42	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	13.47	kN	No		
HEP :	25.0 %	12.95	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	10.51	kN	Yes 15	Times	
Ref :		10.36	kN			
LCP :	1.5 %	10.20	kN	Yes 15	Times	
LEP :	25.0 %	7.77	kN	Yes 35	Rotations 35	Tablets
LSP :	30.0 %	7.25	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.07	kN	Min :	1.02	kN	Punch NO.;	6
SD :	2.10	%	Max :	1.13	kN	Punch NO.;	34
Mean Main Pressure :	10.36	kN	Min :	9.16	kN	Punch NO.;	46
SD :	5.30	%	Max :	12.14	kN	Punch NO.;	73
Filling Depth :	Increase ;	39	Times	Decrease ;	21	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.23	mm	Main Thickness ;	2.24	mm
Filling Depth :	5.46	mm	Current Cam :	Cam B	
Main Air pressure :	0.757	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	54	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.15	kN		
	Max ;	0.19	kN	Max Punch ;	34
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.12	kN	Max Punch ;	55
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.06	kN	Max Punch ;	37

Tablet Data (N/A)

Total Counter :	500360	Tablets			
A.W.C Counter :	484538	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	223 (0.0%)	Tablets
GOOD :	484314 (100.0%)	Tablets			