

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	pb97604	Batch NO. :	SHM2502750
Print Interval :	50000 Tablets	Running Time :	07 Hour 40 Min 38 Sec
Total Counter :	1979088	Total Running Time :	2034 Hour 23 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	42	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.70	kN	No		
HEP :	25.0 %	17.02	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	13.82	kN	Yes 15	Times	
Ref :		13.61	kN			
LCP :	1.5 %	13.41	kN	Yes 15	Times	
LEP :	25.0 %	10.21	kN	No 35	Rotations 35	Tablets
LSP :	30.0 %	9.53	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.40	kN	Min :	1.34	kN	Punch NO.;	25
SD :	1.30	%	Max :	1.45	kN	Punch NO.;	18
Mean Main Pressure :	13.59	kN	Min :	11.22	kN	Punch NO.;	64
SD :	4.20	%	Max :	15.10	kN	Punch NO.;	68
Filling Depth :	Increase ; 9	Times	Decrease ; 73	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.19	mm	Main Thickness ;	2.20	mm
Filling Depth :	5.87	mm	Current Cam :	Cam B	
Main Air pressure :	0.783	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	71	Min			
Lower Punch Remain Time (S2):	12	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.11	kN		
	Max ;	0.17	kN	Max Punch ;	27
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.13	kN	Max Punch ;	56
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.07	kN	Max Punch ;	32

Tablet Data (N/A)

Total Counter :	1979088	Tablets			
A.W.C Counter :	1961569	Tablets			
HEP :	163 (0.0%)	Tablets	LEP :	1038 (0.1%)	Tablets
GOOD :	1960368 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA 50MG STSH4A00
User ID :	pb97604	Batch NO. :	SHM2502750
Print Interval :	50000 Tablets	Running Time :	07 Hour 40 Min 38 Sec
Total Counter :	1979088	Total Running Time :	2034 Hour 23 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	42	%	Manual ;	30	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		6000000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		60.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		1.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.58	kN	No		
HEP :	25.0 %	15.94	kN	Yes 10	Rotations 20	Tablets
HCP :	1.5 %	12.94	kN	Yes 15	Times	
Ref :		12.75	kN			
LCP :	1.5 %	12.56	kN	Yes 15	Times	
LEP :	25.0 %	9.56	kN	Yes 35	Rotations 35	Tablets
LSP :	30.0 %	8.93	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.05	kN	Min :	1.01	kN	Punch NO.;	62
SD :	2.00	%	Max :	1.11	kN	Punch NO.;	24
Mean Main Pressure :	12.96	kN	Min :	11.54	kN	Punch NO.;	50
SD :	4.70	%	Max :	15.16	kN	Punch NO.;	73
Filling Depth :	Increase ;	13	Times	Decrease ;	16	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.23	mm	Main Thickness ;	2.24	mm
Filling Depth :	5.59	mm	Current Cam :	Cam B	
Main Air pressure :	0.783	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	71	Min			
Lower Punch Remain Time (S2):	12	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.11	kN		
	Max ;	0.18	kN	Max Punch ;	55
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.13	kN	Max Punch ;	56
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.07	kN	Max Punch ;	32

Tablet Data (N/A)

Total Counter :	1979088	Tablets			
A.W.C Counter :	1961569	Tablets			
HEP :	163 (0.0%)	Tablets	LEP :	1038 (0.1%)	Tablets
GOOD :	1960368 (99.9%)	Tablets			